



Portable Peak Meter

Highlights

- Accommodates most transducers with output ranging from 0.8 to 5.0 mV/V
- Compatible with most strain gage torque transducers & load cells
- Stores and recalls up to five readings
- Data can be used to create statistical process control charts
- Calibrates using external shunt calibration resistor
- Reverse switch allows the measurement of torque in counter-clockwise direction
- Three selectable decimal point positions
- Analog output receptacle

Applications

- Monitoring Dynamic or Static Torque Applied to Threaded Fasteners
- Monitoring Compression or Tension Force



RS Technologies, a division of PCB Load & Torque, Inc., Model 910 Portable Peak Meter is a versatile, battery-powered, single channel meter designed to monitor and store peak readings from torque or force transducers. The meter has five peak memories to store and recall the peak or maximum torque or force on five cycles. The track mode is used when peak hold is not needed, such as during calibration or when it is desirable to view the transducer output continuously. The span adjustment allows the peak or track readings to be in direct engineering units. The unit offers manual zero adjustment. The unit includes a nickel-cadmium rechargeable battery that offers eight hours of continuous operation before requiring a charge. Model 910 can accommodate most transducers with output ranging from 0.8 to 5.0 mV/V. The unit features external shunt calibration resistor to calibrate, and a switch which allows the measurement of torque in a counter-clockwise direction.

Model 910 is specifically designed to operate with PCB Load & Torque, Inc. strain gage load cells, since it can read force in numerous engineering units. For example, Model 910 Portable Peak Meter can be used with a PCB® Pedal Force Load Cell for vehicle braking tests.

When used with PCB® Stationary Torque Transducers, Model 910 Portable Peak Meter displays applied hand torque.

RS Technologies provides calibration services for this and their other torque and force products at its A2LA Accredited Calibration Laboratory in Farmington Hills, Michigan.

As with all PCB® instrumentation, these products are complemented with toll-free applications assistance, 24-hour technical service, and are backed by a no-risk policy that guarantees total customer satisfaction or your money refunded.



Model 910	
Instrument Accuracy	±0.5% FS
Non-linearity	±0.5 % FS
Temperature Range	0 to +60°C -18 to +16°F
Battery	8 Hour Life
Recharger	120 VAC, 14 Hours for Complete Recharge
Input Sensitivity	350 to 1000 Ohm, Full Bridge
Input Signal	0.8 to 5.0 mV/V
Display	0.6-in High LED, 3 ½-digits, 1999 Maximum Display
Operating Modes	Peak, Track
Bridge Excitation	10 VDC
Frequency Response	DC to 3200 Hz
Peak Memory Drift	Less than 1.0% FS in 15 Minutes
Calibration	Binding Posts for External Resistor
Output Jack	±2.0 VDC
Size (H x W x D)	9.5 x 4.2 x 2.8 in 241 x 107 x 71 mm
Weight	1.4 lb 635 gm
Supplied Accessories	
Shoulder Strap, Battery Charger, Instruction Manual, & A2LA Accredited Calibration Certificate	



RS Technologies, a division of PCB Load & Torque, Inc, is a leading manufacturer of a complete line of rotary and stationary torque sensors, hand torque wrenches, measuring instruments, and threaded fastener torque-tension testing systems with over 40 years of history serving the product assembly and fastener manufacturing community. From ready-to-ship stock products, to custom-made specials, RS Technologies proudly stands behind all products with services customers value most, including calibration services from our A2LA accredited laboratory, 24-hour technical support, a global distribution network, and the industry's only commitment to Total Customer Satisfaction. For more information, please visit www.pcbloadtorque.com.



RS TECHNOLOGIES
A DIVISION OF PCB LOAD & TORQUE, INC.
 24350 Indoplex Circle, Farmington Hills, MI 48335
 Toll-Free: 888-684-2894 Fax: 248-888-8266
 E-mail: rsinfo@pcbloadtorque.com
www.pcbloadtorque.com
 ISO 9001 CERTIFIED ■ A2LA ACCREDITED to ISO 17025

The Global Leader in Sensors and Instrumentation For All Your Applications



Toll-Free in USA 800-828-8840
 E-mail info@pcb.com



Toll-Free in USA 800-959-4464
 E-mail imi@pcb.com



Toll-Free in USA 888-258-3222
 E-mail sales@larsondavis.com



Toll-Free in USA 800-860-4867
 E-mail info@modalshop.com



24350 Indoplex Circle, Farmington Hills, MI 48335 USA
Toll-Free in USA 866-684-7107
24-hour SensorLineSM 716-684-0001
Fax 248-888-8266 E-mail ltinfo@pcbloadtorque.com
www.pcbloadtorque.com
 ISO 9001 CERTIFIED ■ A2LA ACCREDITED to ISO 17025



Visit www.pcb.com to locate
 your nearest sales office

© 2012 PCB Group, Inc. In the interest of constant product improvement, specifications are subject to change without notice. PCB, ICP, Modally Tuned, Spindler, Swiveler and TORKDISC are registered trademarks of PCB Group. SoundTrack LXT, Spark and Blaze are registered trademarks of PCB Piezotronics. SensorLine is a service mark of PCB Group. All other trademarks are property of their respective owners.