

4-Digit Indicator with Sensor Power Supply

For use with Voltage Output Pressure Transducers or 4 to 20 mA Current Output Pressure Transmitters

- Provides 24 VDC Excitation for Voltage Output Pressure Transducers or Current Output Pressure Transmitters
- High Visibility, 4-digit, Fully Scalable, LED Display
- Straightforward, Menu-Driven Set-Up
- Optional User-Programmable Set Points with Relays and LED Alarm Status Indicators
- Optional 4-20 mA Output for Process Recorder or PLC

The **Model 100A02** is a 1/8 DIN, panel-mount indicator / power supply that has been specifically designed for use with internally amplified, voltage-output pressure transducers, or 4 to 20 mA current-output pressure transmitters. The unit operates from universal AC or DC power, provides 24 VDC sensor excitation, and displays measurements on a bright red, 4-digit, LED display. Additional features include overload indication and peak hold with reset capability.

Optional features include a 4-20 mA output signal for remote monitoring or recording purposes; two user-programmable, set-point activated, relay contacts for alarm, shut-down, or control purposes; individual LED indicators of set-point status; and a clear, NEMA 4X front cover.

The Model 100A02 represents a cost effective approach for process indication, alarm, and control of pressure and level.

As with all equipment from PCB®, the Model 100A02 is complemented with toll-free applications assistance, 24-hour customer service, and is backed by a **Total Customer Satisfaction** guarantee.



Series 100A02 panel-mount indicator provides excitation power for pressure transmitters and programmable relays for alarm and control purposes.

Specifications

Performance	
Input Channels	1
Display	4 digit, 0.56 in (14.2 mm) red LED
Set Point Status Indicator	One LED per set point
Decimal Point	Selectable, X•X•X•X•
Scale Factor (for display of enrg. units)	-1999 to +9999
Overrange Indication	Display flash on pos. or neg. overrange
Conversion (update) Rate	5 Hz
Accuracy	± 0.05% of reading, plus 2 counts

Electrical	
Input Signal	0 to 20 VDC or 4 to 20 mA
Sensor / Transmitter Excitation Delivered	24 VDC
Hysteresis (deadband) about Setpoint	± (9999/2) counts from setpoint
Power Required (auto sensing, wide range)	85 to 265 VAC or 95 to 370 VDC
Power Consumption	2.5 watt typical, 3.5 watt max
Warm-Up Time	<2 min

Programmability
 Scale factor, Offset, Decimal point location, Set point adjustment, Peak and valley view and reset, LED brightness, HI or LOW set point relay action, Relay hysteresis

Environmental	
Operating Temperature Range	+32 to +140 °F (0 to +60 °C)
Storage Temperature Range	-4 to +158 °F (-20 to +70 °C)
Humidity (non-condensing)	<95 %

Mechanical	
Size	Bezel: 1/8 DIN (96 × 48 mm)
Depth	4.61 in (117 mm)
Connector Depth (add)	0.47 in (11.8 mm) for right angle block
Connector Depth (add)	0.79 in (20 mm) for straight thru block
Electrical Connections	Screw terminals on removable blocks
Weight	6.5 oz (184 gm)

Options	
Analog Output	4 to 20 mA output signal
NEMA 4X Lens Cover with Key Lock	Field installable
Metal Surround Case	Must be factory installed
Relays (individually adjustable HI or LOW)	Two 5 Amp Form A

How to order

Base Model	
100A02	Indicator / Power Supply
Input	
0	0 to 20 VDC with 24 VDC excitation delivered to sensor / transmitter
1	4 to 20 mA with 24 VDC excitation delivered to sensor / transmitter
Power Required	
0	85 to 265 VAC or 95 to 370 VDC
Analog Output	
0	None
1	Isolated 16 bit user scalable 4-20 mA output signal
Relay Outputs	
0	None
1	Two 5 Amp Form A relays
Accessories	
00	None
01	NEMA 4X, clear, lockable, splash-proof front cover
02	Metal surround case - includes screw mounting clips
03	NEMA 4X, clear front cover and metal surround case
Example	
100A02	0 0 0 0 01 Standard indicator with clear, NEMA 4X front cover

CE This product conforms to applicable European Directives for CE marking.



3425 Walden Avenue, Depew, NY 14043-2495 USA
Pressure Division toll-free 888-684-0011
24-hour SensorLineSM 716-684-000
Fax 716-686-9129 E-mail pressure@pcb.com
Web site www.pcb.com

ISO 9001 CERTIFIED A2LA ACCREDITED to ISO 17025

© 2003 PCB Group, Inc. In the interest of constant product improvement, specifications are subject to change without notice. PCB and ICP are a registered trademarks of PCB Group, Inc. SensorLine is a service mark of PCB Group, Inc. All other trademarks are properties of their respective owners.

The Pressure Division of PCB® Piezotronics, Inc. specializes in the development, application, and support of piezoelectric and thin film pressure sensors, transducers, and transmitters for dynamic and static pressure measurement, test, monitoring, and control requirements. This product focus, coupled with the strengths and resources of PCB, permits the Pressure Division to offer timely response to client's needs, exceptional customer service, 24-hour technical assistance, and a **Total Customer Satisfaction** guarantee.

Visit **www.pcb.com** to locate your nearest sales office