

Performance	ENGLISH	SI	
Measurement Range(for ±5V output)	100 psi	689.5 kPa	[1]
Useful Overrange(for ± 10V output)	200 psi	1,379 kPa	[2]
Sensitivity(± 15 %)	50 mV/psi	7.25 mV/kPa	
Maximum Pressure(Total)	7.5 kpsi	51,711 kPa	[3]
Maximum Pressure(step)	1,000 psi	6,900 kPa	
Resolution	2 mpsi	0.014 kPa	[4]
Resonant Frequency	≥ 250 kHz	≥ 250 kHz	
Rise Time(Reflected)	≤ 2.0 μ sec	≤ 2.0 μ sec	
Non-Linearity	≤ 1.0 % FS	≤ 1.0 % FS	[5]
<b>Environmental</b>			
Acceleration Sensitivity	≤ 0.002 psi/g	≤ 0.0014 kPa/(m/s <sup>2</sup> )	
Temperature Range(Operating)	-320 to 212 °F	-196 to 100 °C	
Temperature Coefficient of Sensitivity	≤ 0.06 %/°F	≤ 0.108 %/°C	
Maximum Flash Temperature	3,000 °F	1648.89 °C	
Maximum Vibration	2,000 g pk	19,613 m/s <sup>2</sup> pk	
Maximum Shock	20,000 g pk	196,133 m/s <sup>2</sup> pk	
<b>Electrical</b>			
Discharge Time Constant(at room temp)	≥ 1.0 sec	≥ 1.0 sec	
Excitation Voltage	15 to 30 VDC	15 to 30 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Impedance	100 Ohm	100 Ohm	
Output Bias Voltage	3 to 8 VDC	3 to 8 VDC	
<b>Physical</b>			
Housing Material	304L/316L Stainless Steel	304L/316L Stainless Steel	
Thread Adaptor Material	Vascomax C-300	Vascomax C-300	
Diaphragm	316L Stainless Steel	316L Stainless Steel	
Sealing	Welded Hermetic	Welded Hermetic	
Electrical Connector	10-32 Coaxial Jack	10-32 Coaxial Jack	
Weight	0.9 oz	25 gm	

**OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

**NOTES:**

[1]-5V output may be limited by the output bias.  
 [2]For +10 volt output, minimum 24 VDC supply voltage required. Negative 10 volt output may be limited by output bias.  
 [3]Due to high sensitivity, the static pressure should be applied and removed very slowly. Rate should prevent more than 10 Volt change in output until Output Bias Voltage returns to normal (approximately 15 times discharge time constant).  
 [4]Typical.  
 [5]Zero-based, least-squares, straight line method.  
 [6]See PCB Declaration of Conformance PS023 for details.



Entered: LK	Engineer: NJL	Sales: RWM	Approved: RPF	Spec Number:
Date: 07/09/2020	Date: 07/09/2020	Date: 07/09/2020	Date: 07/09/2020	70091

**Phone: 716-684-0001**  
**Fax: 716-684-0987**  
**E-Mail: info@pcb.com**

3425 Walden Avenue, Depew, NY 14043

All specifications are at room temperature unless otherwise specified.  
 In the interest of constant product improvement, we reserve the right to change specifications without notice.  
 ICP® is a registered trademark of PCB Piezotronics, Inc.