

	<u>ENGLISH</u>	<u>SI</u>
Performance		
Connector Style	MS3116	MS3116
Connection Type	Multi-conductor 2-socket Plug with Female Contact	Multi-conductor 2-socket Plug with Female Contact
Coupling Method	Bayonet	Bayonet
Strain Relief	Clamp	Clamp
Environmental		
Temperature Range	-67 to +257 °F	-55 to +125 °C
Electrical		
Insulation Resistance	≥ 5 Gohm	≥ 5 Gohm
Physical		
ROHS Compliant	No	No
Housing Material	Aluminum Alloy	Aluminum Alloy
Finish	Olive drab chromate over cadmium	Olive drab chromate over cadmium
Size (OD x Length)	0.75 in x 1.76 in	19.1 mm x 44.7 mm
Weight	0.62 oz	17.6 gm
<i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i>		

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:
[1] Typical.

Entered: <i>SA</i>	Engineer: <i>mjm</i>	Sales: <i>mjm</i>	Approved: <i>EB</i>	Spec Number:
Date: <i>8-6-09</i>	Date: <i>7-28-09</i>	Date: <i>7-28-09</i>	Date: <i>7-28-09</i>	43706



IMI SENSORS
A PCB PIEZOTRONICS DIV.

IMI Sensors
3425 Walden
Depew, NY 14043
UNITED STATES
Phone: 800-959-4464
Fax: 716-684-3823
E-Mail: imi@pcb.com
Web site: <http://www.imi-sensors.com>