

Model Number <b>261A01</b>	<b>3-COMPONENT ICP® SENSOR</b>	Revision: B ECN #: 33704
-------------------------------	--------------------------------	-----------------------------

	<u>ENGLISH</u>	<u>SI</u>	
<b>Performance</b>			
Sensitivity(± 20 %)(z axis)	2.5 mV/lb	0.56 mV/N	[1]
Sensitivity(± 20 %)(x or y axis)	10 mV/lb	2.25 mV/N	[1]
Measurement Range(z axis)	1000 lb	4.45 kN	
Measurement Range(x or y axis)	500 lb	2.22 kN	
Maximum Force(z axis)	1320 lb	5.87 kN	
Maximum Force(x or y axis)	660 lb	2.94 kN	
Maximum Moment(z axis)	14 ft-lb	18.98 N-m	
Maximum Moment(x or y axis)	13 ft-lb	17.63 N-m	
Broadband Resolution(z axis)	0.006 lb-rms	0.027 N-rms	[2]
Broadband Resolution(x or y axis)	0.002 lb-rms	0.0089 N-rms	[2]
Upper Frequency Limit	10 kHz	10 kHz	
Low Frequency Response(-5 %)(z-axis)	0.01 Hz	0.01 Hz	
Low Frequency Response(-5 %)(x or y axis)	0.001 Hz	0.001 Hz	
Non-Linearity	≤ 1 % FS	≤ 1 % FS	[3]
Cross Talk(between x and y axis)	± 3 %	± 3 %	
Cross Talk(between (x or y axis) and z axis)	± 5 %	± 5 %	
<b>Environmental</b>			
Temperature Range	-65 to +250 °F	-54 to +121 °C	
<b>Electrical</b>			
Full Scale Output(Z Direction)	± 2.5 VDC	± 2.5 VDC	
Full Scale Output(X and Y Direction)	± 5 VDC	± 5 VDC	
Discharge Time Constant(z axis)	≥ 50 sec	≥ 50 sec	
Discharge Time Constant(x or y axis)	≥ 500 sec	≥ 500 sec	
Excitation Voltage(all channels)	20 to 30 VDC	20 to 30 VDC	
Constant Current Excitation(all channels)	2 to 20 mA	2 to 20 mA	
Output Impedance	≤ 100 ohm	≤ 100 ohm	
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC	
Spectral Noise(1 Hz)(X & Y)	0.00003 lb/√Hz	0.00134 N/√Hz	
Spectral Noise(10 Hz)(X & Y)	0.00015 lb/√Hz	0.000668 N/√Hz	
Spectral Noise(100 Hz)(X & Y)	0.00005 lb/√Hz	0.000223 N/√Hz	
Spectral Noise(1 kHz)(X & Y)	0.000015 lb/√Hz	0.0000668 N/√Hz	
Spectral Noise(1 Hz)(Z)	0.0015 lb/√Hz	0.0068 N/√Hz	
Spectral Noise(10 Hz)(Z)	0.00055 lb/√Hz	0.00245 N/√Hz	
Spectral Noise(100 Hz)(Z)	0.0002 lb/√Hz	0.000891 N/√Hz	
Spectral Noise(1 kHz)(Z)	0.000055 lb/√Hz	0.000245 N/√Hz	
Output Polarity	Positive	Positive	
<b>Physical</b>			
Stiffness(z axis)	10 lb/μin	1.75 kN/μm	[2]
Stiffness(x or y axis)	4 lb/μin	0.7 kN/μm	[2]
Weight	13.60 oz	386 gm	
Housing Material	Stainless Steel	Stainless Steel	
Sealing	Hermetic	Hermetic	
Electrical Connector	4-Pin	4-Pin	
Electrical Connection Position	Side	Side	

**OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

**M** - Metric Mount

**W** - Water Resistant Cable

Electrical Connection Position Side      Side

**NOTES:**

[1] Sensitivites are for listed preload. Sensitivites may vary ±5% depending on preload used.

[2] Typical.

[3] Zero-based, least-squares, straight line method.

[4] See PCB Declaration of Conformance PS023 for details.

Entered: <i>iomw</i>	Engineer: <i>mjh</i>	Sales: <i>kwjw</i>	Approved: <i>CB</i>	Spec Number:
Date: <i>8/17/10</i>	Date: <i>8/17/10</i>	Date: <i>8/17/10</i>	Date: <i>8/17/10</i>	<b>26966</b>



All specifications are at room temperature unless otherwise specified.  
 In the interest of constant product improvement, we reserve the right to change specifications without notice.  
 ICP® is a registered trademark of PCB Group, Inc.

**PCB PIEZOTRONICS**  
**FORCE / TORQUE DIVISION**

3425 Walden Avenue, Depew, NY 14043

Phone: 716-684-0001  
 Fax: 716-684-8877  
 E-Mail: force@pcb.com