

	ENGLISH	SI	
Performance			
Sensitivity(± 10 %)	100 mV/g	10.2 mV/(m/s ²)	
Measurement Range	± 50 g pk	± 490 m/s ² pk	
Frequency Range(± 5 %)	2 to 5000 Hz	2 to 5000 Hz	
Frequency Range(± 10 %)	1 to 10,000 Hz	1 to 10,000 Hz	
Frequency Range(± 3 dB)	0.5 to 12,000 Hz	0.5 to 12,000 Hz	
Resonant Frequency	≥ 25 kHz	≥ 25 kHz	
Broadband Resolution(1 to 10,000 Hz)	0.0005 g rms	0.005 m/s ² rms	[1]
Non-Linearity	≤ 1 %	≤ 1 %	[2]
Transverse Sensitivity	≤ 5 %	≤ 5 %	[3]
Environmental			
Overload Limit(Shock)	± 5000 g pk	± 49,050 m/s ² pk	
Temperature Range(Operating)	-65 to +250 °F	-54 to +121 °C	
Temperature Response	See Graph	See Graph	[1]
Electrical			
Excitation Voltage	22 to 30 VDC	22 to 30 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Impedance	≤ 100 Ohm	≤ 100 Ohm	
Output Bias Voltage	11 to 16 VDC	11 to 16 VDC	
Discharge Time Constant	0.5 to 2.0 sec	0.5 to 2.0 sec	
Settling Time(within 10% of bias)	<20 sec	<20 sec	
Spectral Noise(1 Hz)	240 µg/√Hz	2350 (µm/sec ²)/√Hz	[1]
Spectral Noise(10 Hz)	65 µg/√Hz	640 (µm/sec ²)/√Hz	[1]
Spectral Noise(100 Hz)	15 µg/√Hz	150 (µm/sec ²)/√Hz	[1]
Spectral Noise(1 kHz)	5 µg/√Hz	50 (µm/sec ²)/√Hz	[1]
Electrical Isolation(Base)	≥ 10 ⁸ Ohm	≥ 10 ⁸ Ohm	
Physical			
Size (Height x Length x Width)	0.40 in x 0.70 in x 0.63 in	10.2 x 17.8 mm x 15.9 mm	[1]
Weight	0.39 oz	11 gm	
Sensing Element	Quartz	Quartz	
Sensing Geometry	Shear	Shear	
Housing Material	Titanium	Titanium	
Sealing	Hermetic	Hermetic	
Electrical Connector	10-32 Coaxial Jack	10-32 Coaxial Jack	
Electrical Connection Position	Side	Side	
Mounting	Through Hole	Through Hole	

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

M - Metric Mount
Supplied Accessory : Model M039A22 Allen wrench for use with M3 thread (1) replaces Model 039A22

Supplied Accessory : Model M081B45 Insulated cap screw, M3x0.5 thd x 5/8" long (for Model M355B02) (1) replaces Model 081B45

T - TEDS Capable of Digital Memory and Communication Compliant with IEEE P1451.4

TLA - TEDS LMS International - Free Format

TLB - TEDS LMS International - Automotive Format

TLC - TEDS LMS International - Aeronautical Format

TLD - TEDS Capable of Digital Memory and Communication Compliant with IEEE 1451.4

Excitation Voltage	24 to 30 VDC	24 to 30 VDC
Output Bias Voltage	11.7 to 17 VDC	11.7 to 17 VDC

NOTES:

[1] Typical.

[2] Zero-based, least-squares, straight line method.

[3] Transverse sensitivity is typically ≤ 3%.

[4] See PCB Declaration of Conformance PS023 for details.

SUPPLIED ACCESSORIES:


Model 039A22 Allen wrench, 7/64" hex (1)

Model 080A109 Petro Wax (1)

Model 081B45 Insulated cap screw, 6-32 thd x 5/8" long (for Model 355B02) (1)

Model ACS-1 NIST traceable frequency response (10 Hz to upper 5% point). (1)

Entered: LK Engineer: BAM Sales: WDC Approved: BAM Spec Number:
Date: 9/16/2016 Date: 9/16/2016 Date: 9/16/2016 Date: 9/16/2016 **20469**



All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.
ICP® is a registered trademark of PCB Group, Inc.