

	<u>ENGLISH</u>	<u>SI</u>	
Performance			
Sensitivity(± 5 %)	40 mV/g	4.1 mV/(m/s ²)	
Measurement Range	± 50 g pk	± 490.5 m/s ² pk	
Frequency Range(± 3 dB)	0 to 2000 Hz	0 to 2000 Hz	[2]
Frequency Range(± 3 dB)	0 to 1000 Hz	0 to 1000 Hz	[5]
Phase Response(100 Hz)	<10 °	<10 °	
Broadband Resolution(0.5 to 100 Hz)	1.0 mg rms	0.010 m/s ² rms	[2]
Non-Linearity	≤ 1 %	≤ 1 %	[6]
Transverse Sensitivity	≤ 5 %	≤ 5 %	
Environmental			
Overload Limit(Shock)	± 5000 g pk	± 49,050 m/s ² pk	
Temperature Range(Operating)	-65 to +250 °F	-54.0 to +121 °C	
Temperature Range(Storage)	-65 to +250 °F	-54.0 to +121 °C	
Temperature Coefficient of Sensitivity	± 3 %	± 3 %	[3]
Zero g Offset Temperature Coefficient	± 2 % FSO	± 2 % FSO	[3][4]
Base Strain Sensitivity(Measured at 250 µε)	.001 g/µε	.01 (m/s ²)/µε	[2]
Magnetic Sensitivity	40 µg/gauss	3.9 (m/s ²)/Tesla	[2]
Electrical			
Excitation Voltage	6 to 30 VDC	6 to 30 VDC	
Current Consumption	≤ 10 mA	≤ 10 mA	
Output Impedance	≤ 120 Ohm	≤ 120 Ohm	
Offset Voltage(0 g)	± 80 mVDC	± 80 mVDC	[1]
Spectral Noise(1 to 100 Hz)	200 µg/√Hz	1962 (µm/sec ²)/√Hz	[2]
Electrical Isolation(Case)	>10 ⁸ Ohm	>10 ⁸ Ohm	
Physical			
Housing Material	Titanium	Titanium	
Sealing	Hermetic	Hermetic	
Size (Height x Length x Width)	0.45 in x 0.85 in x 0.85 in	11.4 mm x 21.6 mm x 21.6 mm	
Weight	0.58 oz	16.3 gm	
Electrical Connector	4-Pin	4-Pin	
Electrical Connection Position	Side	Side	
Mounting	Through Holes (2)	Through Holes (2)	

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

[1]Offset tolerance is based on 10 ft of 010 test cable.
 [2]Typical.
 [3]-65 to +250 °F, ref. 75 °F (-54 to +121 °C, ref. 24 °C)
 [4]FSO = Full Scale Output over the Measurement Range (4VDC).
 [5]Minimum, verified with Calibration data.
 [6]Least-squares, straight line method, % FSO.
 [7]See PCB Declaration of Conformance PS027 for details.

SUPPLIED ACCESSORIES:

Model 080A152 Easy Mount Clip (1)
 Model 081A113 Mounting screw assembly (2)
 Model ACS-145 Phase and Amplitude Calibration from 2 Hz to ±3 dB of frequency range (1)
 Model M081A113 Mounting screw assembly (2)

Entered: AP	Engineer: JJD	Sales: RWM	Approved: NJF	Spec Number:
Date: 3/27/2015	Date: 3/27/2015	Date: 3/27/2015	Date: 3/27/2015	60026



All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.
 ICP® is a registered trademark of PCB Group, Inc.



Phone: 716-684-0001
Fax: 716-684-0987
E-Mail: info@pcb.com