

	ENGLISH	SI	
<b>Performance</b>			
Nominal Microphone Diameter	1/2"	1/2"	
Frequency Response Characteristic	Pressure	Pressure	
Open Circuit Sensitivity(± 2 dB)	-38.0 dB re 1 V/Pa	-38.0 dB re 1 V/Pa	[3]
Open Circuit Sensitivity	12.6 mV/Pa	12.6 mV/Pa	[3]
Frequency Range(± 1 dB)	4 to 7500 Hz	4 to 7500 Hz	
Frequency Range(± 2 dB)	3.15 to 20,000 Hz	3.15 to 20,000 Hz	
Lower Limiting Frequency(-3 dB)	1.0 to 2.4 Hz	1.0 to 2.4 Hz	
Resonant Frequency(90° Phase Shift)	19,000 Hz	19,000 Hz	[1]
Inherent Noise	18 dB(A) re 20 µPa	18 dB(A) re 20 µPa	[1]
Dynamic Range(3% Distortion Limit)	162 dB re 20 µPa	162 dB re 20 µPa	[1]
Standards Designation(IEC 61094-4)	WS2P	WS2P	
<b>Environmental</b>			
Temperature Range(Operating)	-40 to +248 °F	-40 to +120 °C	
Temperature Coefficient of Sensitivity(+14 to +122°F (-10 to +50°C))	0.004 dB/°F	0.008 dB/°C	[1][3]
Static Pressure Coefficient	-0.006 dB/kPa	-0.006 dB/kPa	[1][3]
Humidity Coefficient of Sensitivity(0 to 100%, non-condensing)	± 0.001 dB/%RH	± 0.001 dB/%RH	[3]
Influence of Axial Vibration(0.1g (1 m/s <sup>2</sup> ))	66 dB re 20 µPa	66 dB re 20 µPa	[1]
<b>Electrical</b>			
Capacitance(Polarized)	14 pF	14 pF	[1]
Polarization Voltage	0 V	0 V	[2]
<b>Physical</b>			
Housing Material	Stainless Alloy	Stainless Alloy	
Venting	Rear	Rear	
Mounting Thread(Preamplifier)	0.4606 - 60 UNS	11.7 mm - 60 UNS	
Mounting Thread(Grid)	0.5 - 60 UNS	12.7 mm - 60 UNS	
Size (Diameter x Height)(with grid)	0.52 in x 0.48 in	13.2 mm x 12.3 mm	
Size (Diameter x Height)(without grid)	0.5 in x 0.46 in	12.7 mm x 11.8 mm	
Weight	0.23 oz	6.5 gm	[1]
<i>All specifications are at room temperature unless otherwise specified.            In the interest of constant product improvement, we reserve the right to change specifications without notice.</i>			

**OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

**NOTES:**  
 [1] Typical.  
 [2] Pre-polarized  
 [3] re 250 Hz

**SUPPLIED ACCESSORIES:**  
 Model ACS-20 Calibration of Precision Condenser Microphones (1)

Entered: LK      Engineer: MT      Sales: MV      Approved: MT      Spec Number:  
 Date: 10/13/2016    Date: 10/13/2016    Date: 10/13/2016    Date: 10/13/2016      **57497**



3425 Walden Avenue, Depew, NY 14043

**Phone: 716-684-0001**  
**Fax: 716-684-0987**  
**E-Mail: info@pcb.com**