



## TORQUE MONITORING FOR ELECTRIC DRIVE SHIPS

**MEASUREMENT FOR HIGH EMI ENVIRONMENTS** 

## **Application: Torque Monitoring for Electric Drive Ships (in a high EMI environment)**

Wireless torque measurement for new designs of large ships

**Industry:** Marine

**Product:** AT-4400

Parameters measured: Torque

When a government laboratory needed to monitor torque in the presence of high EMI from variable speed drive circuitry, they found that their legacy FM telemetry systems were not able to reliably transfer data. In searching for an alternative, they found Accumetrics' website, and recognized that digital telemetry would be a likely solution. The AT-4400 was identified as a unit of choice. The needs for the system were:

- No dropouts (gaps in data) or distortion due to EMI interference
- Long term operation (no batteries)
- High resolution

A demonstrator AT-4400 was tested in an EMI susceptibility chamber and found to far surpass the older existing telemetry systems' EMI capability during swept frequency testing. An AT-4400 system was obtained for a large drive shaft and has been shown to be capable of withstanding modern ship operating requirements as seen in DD(X) and other high power/ highly noise prone AC drive designs.

The AT-4400 samples at 26,484 samples per second, and has outstanding accuracy, noise floor, and resolution (16 bit).







- The top picture shows a split clamp-collar glass laminate (G10) transmitter collar surrounded by a rigid phenolic pickup loop for induction power and data.
- The middle picture shows the front of the Receiver, with on-the-fly shunt calibration control (controlling a shunt resistor at the rotating transmitter).
- The bottom picture shows the AT-4400 Receiver rear view. The Receiver is the digital to analog 0 +/- 10V output device. The open panel shows the fine adjust gain, offset, and symmetry controls, the coarse gain and offset controls, and the output signal filter control.

