



WATER & WASTEWATER TREATMENT EQUIPMENT



WATER & WASTEWATER TREATMENT EQUIPMENT

Municipal water authorities oversee a vast range of infrastructure, including wastewater treatment plants, water treatment plants, lift stations, pump stations, storage tanks and miles of sewer/water pipelines. The efficient and uninterrupted operation of the system is essential in order for water authorities to stay in compliance with local and federal drinking water and wastewater discharge/treatment laws.

The infrastructure system includes a variety of rotating assets, including blowers/fans, motors and pumps. Performing vibration analysis on this equipment can detect developing faults early so that they can be addressed before causing catastrophic failure.

- Blowers/Fans- Friction, imbalance, looseness/misalignment
- Motors- Bearing issues, electrical issues, imbalance, looseness/misalignment
- Pumps- Cavitation, imbalance, looseness/misalignment

Many water authorities already utilize a SCADA (supervisory control and data acquisition) system to monitor and control the process. Vibration transmitters with a current output can be easily integrated into that existing system in order to collect and record vibration data. Vibration transmitters output an overall value, which does not require extensive mathematical analysis to interpret and is well suited for the knowledge level of process control generalists within a facility.

For those facilities with vibration analysis capabilities and resources, a wide variety of accelerometers are available that can be used for route-based measurements in conjunction with a third-party handheld data collector or for permanent installations in conjunction with online data acquisition systems.

VIBRATION TRANSMITTERS

CE



4-20 mA OUTPUT SENSOR

SERIES 64X

- Peak, RMS velocity or acceleration
- 0-0.5, 0-1, 0-2 ips or 0-5, 0-10 g measurement ranges available
- Intrinsically safe versions available

CE



4-20 mA OUTPUT SENSOR, M12 CONNECTOR

MODEL 655A9X, 656A9X

- Peak or RMS velocity
- Frequency response up to 2 kHz
- Small footprint in height and weight
- Rated to 105 °C

DIN RAIL VIBRATION TRANSMITTERS



CE



VIBRATION TRANSMITTER

MODEL 682C03

- Outputs 4-20 mA signals for overall vibration and temperature
- ICP® accelerometer input
- Analog vibration output via front BNC



CE



BEARING FAULT DETECTOR

MODEL 682C05

- Provide early warning of bearing and gear faults
- ICP® accelerometer input
- Outputs 4-20 mA signals for true peak acceleration and overall vibration

ICP® ACCELEROMETERS



CE



THE SWIVELER® ACCELEROMETER

MODEL 607A11

- Waterproof housing, ideal for submersible applications
- Patented 360° swivel mount
- Small footprint and low-profile design
- Intrinsically safe version available

CE



HIGH-FREQUENCY TRIAXIAL ACCELEROMETER

MODEL 639A91

- Frequency response on all three axes up to 13 kHz (± 3 dB)
- Extremely small footprint
- Integral cable version optional
- Intrinsically safe version available



3425 Walden Avenue, Depew, NY 14043 USA

pcb.com/imi-sensors | imi@pcb.com | 800 959 4464 | +1 716 684 0003

© 2024 PCB Piezotronics - all rights reserved. PCB Piezotronics is a wholly-owned subsidiary of Amphenol Corporation. Endevo is an assumed name of PCB Piezotronics of North Carolina, Inc., which is a wholly-owned subsidiary of PCB Piezotronics, Inc. Accumetrics, Inc. and The Modal Shop, Inc. are wholly-owned subsidiaries of PCB Piezotronics, Inc. IMI Sensors and Larson Davis are Divisions of PCB Piezotronics, Inc. Except for any third party marks for which attribution is provided herein, the company names and product names used in this document may be the registered trademarks or unregistered trademarks of PCB Piezotronics, Inc., PCB Piezotronics of North Carolina, Inc. (d/b/a Endevo), The Modal Shop, Inc. or Accumetrics, Inc. Detailed trademark ownership information is available at www.pcb.com/trademarkownership.

IMI-APP-Wastewater-0224