



Model AE

2-socket environmental boot connector (MIL-C-5015 compatible)

Installation and Operating Manual

**For assistance with the operation of this product,
contact the PCB Piezotronics, Inc.**

Toll-free: 716-684-0001

24-hour SensorLine: 716-684-0001

Fax: 716-684-0987

E-mail: info@pcb.com

Web: www.pcb.com



Model Number AE	CABLE CONNECTOR	Revision: B ECN #: 47806
---------------------------	------------------------	-----------------------------

	<u>ENGLISH</u>	<u>SI</u>
Performance		
Connector Style	MIL-C-5015	MIL-C-5015
Connector Style	Multi-conductor	Multi-conductor
Connection Type	2-socket	2-socket
Connection Type	Jack (female socket / recepticle)	Jack (female socket / recepticle)
Coupling Method(Keyed)	Push On	Push On
Strain Relief	Molded Boot	Molded Boot
Environmental		
Temperature Range	-67 to 325 °F	-55 to 163 °C
Ingress Protection	Molded Environmental Boot	Molded Environmental Boot
Enclosure Rating	IP67	IP67
Physical		
ROHS Compliant	Yes	Yes
Size (OD x Length)	0.88 in x 2.4 in	22 mm x 61 mm
Weight	0.88 oz	25 gm
<i>All specifications are at room temperature unless otherwise specified.</i>		
<i>In the interest of constant product improvement, we reserve the right to change specifications without notice.</i>		
ICP® is a registered trademark of PCB Group, Inc.		

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

Entered: LK	Engineer: RB	Sales: MC	Approved: BAM	Spec Number:
Date: 8/27/2018	Date: 8/27/2018	Date: 8/27/2018	Date: 8/27/2018	32140



IMI SENSORS
A PCB PIEZOTRONICS DIV.

IMI Sensors
3425 Walden
Depew, NY 14043
UNITED STATES
Phone: 800-959-4464
Fax: 716-684-3823
E-Mail: imi@pcb.com
Web site: http://www.imi-sensors.com