



Model BP

2-socket, high temperature MS3106 connector w/strain relief (meets MIL-C-5015)

Installation and Operating Manual

**For assistance with the operation of this product,
contact the PCB Piezotronics, Inc.**

Toll-free: 716-684-0001

24-hour SensorLine: 716-684-0001

Fax: 716-684-0987

E-mail: info@pcb.com

Web: www.pcb.com



Model Number BP	CABLE CONNECTOR	Revision: B ECN #: 48970
---------------------------	------------------------	-----------------------------

	<u>ENGLISH</u>	<u>SI</u>
Performance		
Connector Style	MIL-C-5015	MIL-C-5015
Connector Style	Multi-conductor	Multi-conductor
Connection Type	2-socket	2-socket
Connection Type	Jack (female socket / receptacle)	Jack (female socket / receptacle)
Coupling Method	Threaded	Threaded
Coupling Thread	5/8-24 female	5/8-24 female
Strain Relief	Clamp	Clamp
Environmental		
Temperature Range	-320 to +325 °F	-196 to +163 °C
Physical		
ROHS Compliant	Yes	Yes
Size (OD x Length)	0.87 in x 1.78 in	22 mm x 45.21 mm
Weight	1.19 oz	33.87 gm

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

Entered: LK	Engineer: NJF	Sales: MC	Approved: NJF	Spec Number:
Date: 12/14/2018	Date: 12/14/2018	Date: 12/14/2018	Date: 12/14/2018	32477

*All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.*

ICP® is a registered trademark of PCB Group, Inc.



3425 Walden Avenue, Depew, NY 14043

Phone: 716-684-0001
Fax: 716-684-0987
E-Mail: info@pcb.com