


Model Number <b>055BP030BZ</b>	<b>HIGH-TEMP PTFE HEAVY DUTY CABLE ASSEMBLY</b>		Revision NR ECN #:
<b>Performance</b> Cable Style  Number of Conductors Connector Model (sensor side) Connector Style (sensor side) Connection Type (sensor side) Coupling Method (sensor side) Connector Style (termination) <b>Environmental</b> Temperature Range <b>Electrical</b> Capacitance <b>Physical</b> Cable Jacket Diameter Cable Jacket Material Cable Jacket Color Conductor Style  Conductor Material Conductor Diameter (20 AWG) Shield Type Over Bundle  Shield Material Over Bundle Bend Radius (minimum) Weight	<b>ENGLISH</b> Multi Conductor - Shielded 2 Aluminum MIL-C-5015 2-pin Threaded Blunt Cut  -65 to 325 °F 27 pF/ft  0.19 in PTFE Orange Stranded - 19 strands 32 AWG Tin Plated Copper 0.038 in Braid: 85% Minimum Coverage Tin Plated Copper 1.9 in 0.52 oz/ft	<b>SI</b> Multi Conductor - Shielded 2 Aluminum MIL-C-5015 2-pin Threaded Blunt Cut  -55 to 163 °C 89 pF/m  4.83 mm PTFE Orange Stranded - 19 strands 32 AWG Tin Plated Copper 0.965 mm Braid: 85% Minimum Coverage Tin Plated Copper 48.3 mm 47.97 gm/m	<b>Optional Versions</b> (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)
<p><i>All specifications are at room temperature unless otherwise specified.</i></p> <p>In the interest of constant product improvement, we reserve the right to change specifications without notice.</p>			
Entered: ECB Date: 10/06/2011		Engineer: MJN Date: 10/06/2011 Sales: MRS Date: 10/06/2011 Approved: MRS Date: 10/06/2011 Spec Number: <b>N/A</b>	
		3425 Walden Avenue Depew, NY 14043 UNITED STATES Phone: 800-828-8840 Fax: 716-684-0987 E-mail: info@pcb.com Web site: www.pcb.com	