

Model Number AM	CABLE CONNECTOR	Revision: A ECN #: 48813
---------------------------	------------------------	-----------------------------

	ENGLISH	SI
Performance		
Connector Style	MIL-C-5015	MIL-C-5015
Connector Style	Multi-conductor	Multi-conductor
Connection Type	2-socket	2-socket
Connection Type	Jack (female socket / receptacle)	Jack (female socket / receptacle)
Coupling Method	Threaded	Threaded
Coupling Thread	5/8-24 female	5/8-24 female
Strain Relief	Potted	Potted
Environmental		
Temperature Range	-67 to 257 °F	-55 to 125 °C
Physical		
ROHS Compliant	Yes	Yes
Size (OD x Length)	.87 in x 1.4 in	22 mm x 36 mm
Weight	0.49 oz	14 gm
<p><i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i></p> <p>ICP® is a registered trademark of PCB Group, Inc.</p>		

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

Entered: LK	Engineer: KW	Sales: MC	Approved: BAM	Spec Number:
Date: 2/27/2019	Date: 2/27/2019	Date: 2/27/2019	Date: 2/27/2019	32159



IMI SENSORS
A PCB PIEZOTRONICS DIV.

IMI Sensors
3425 Walden
Depew, NY 14043
UNITED STATES
Phone: 800-959-4464
Fax: 716-684-3823
E-Mail: imi@pcb.com
Web site: <http://www.imi-sensors.com>