


Model Number <b>HC</b>	<b>CABLE CONNECTOR</b>			Revision: A ECN #: 48415																																					
<table border="0"> <thead> <tr> <th data-bbox="142 212 512 240"><b>Performance</b></th> <th data-bbox="512 212 835 240"><u>ENGLISH</u></th> <th data-bbox="835 212 1119 240"><u>SI</u></th> </tr> </thead> <tbody> <tr> <td>Connector Style</td> <td>3116</td> <td>3116</td> </tr> <tr> <td>Connector Style</td> <td>Multi-conductor</td> <td>Multi-conductor</td> </tr> <tr> <td>Connection Type</td> <td>4-socket</td> <td>4-socket</td> </tr> <tr> <td>Coupling Method</td> <td>Bayonet</td> <td>Bayonet</td> </tr> <tr> <td>Strain Relief</td> <td>Clamp</td> <td>Clamp</td> </tr> <tr> <td><b>Environmental</b></td> <td></td> <td></td> </tr> <tr> <td>Temperature Range</td> <td>-67 to +257 °F</td> <td>-55 to +125 °C</td> </tr> <tr> <td><b>Physical</b></td> <td></td> <td></td> </tr> <tr> <td>ROHS Compliant</td> <td>Yes</td> <td>Yes</td> </tr> <tr> <td>Size (OD x Length x Width)</td> <td>0.71 in x 1.76 in x 0.75 in</td> <td>18.03 mm x 44-96 mm x 19.05 mm</td> </tr> <tr> <td>Weight</td> <td>0.79 oz</td> <td>22.34 gm</td> </tr> </tbody> </table> <p data-bbox="142 526 1119 553"><i>All specifications are at room temperature unless otherwise specified.</i></p> <p data-bbox="142 553 1119 581"><i>In the interest of constant product improvement, we reserve the right to change specifications without notice.</i></p> <p data-bbox="142 581 1119 609">ICP® is a registered trademark of PCB Group, Inc.</p>			<b>Performance</b>	<u>ENGLISH</u>	<u>SI</u>	Connector Style	3116	3116	Connector Style	Multi-conductor	Multi-conductor	Connection Type	4-socket	4-socket	Coupling Method	Bayonet	Bayonet	Strain Relief	Clamp	Clamp	<b>Environmental</b>			Temperature Range	-67 to +257 °F	-55 to +125 °C	<b>Physical</b>			ROHS Compliant	Yes	Yes	Size (OD x Length x Width)	0.71 in x 1.76 in x 0.75 in	18.03 mm x 44-96 mm x 19.05 mm	Weight	0.79 oz	22.34 gm	<p data-bbox="1119 212 1927 245" style="text-align: center;"><b>OPTIONAL VERSIONS</b></p> <p data-bbox="1119 245 1927 435">Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.</p>		
<b>Performance</b>	<u>ENGLISH</u>	<u>SI</u>																																							
Connector Style	3116	3116																																							
Connector Style	Multi-conductor	Multi-conductor																																							
Connection Type	4-socket	4-socket																																							
Coupling Method	Bayonet	Bayonet																																							
Strain Relief	Clamp	Clamp																																							
<b>Environmental</b>																																									
Temperature Range	-67 to +257 °F	-55 to +125 °C																																							
<b>Physical</b>																																									
ROHS Compliant	Yes	Yes																																							
Size (OD x Length x Width)	0.71 in x 1.76 in x 0.75 in	18.03 mm x 44-96 mm x 19.05 mm																																							
Weight	0.79 oz	22.34 gm																																							
			Entered: LK	Engineer: RB	Sales: MC	Approved: BAM	Spec Number:																																		
			Date: 8/16/2018	Date: 8/16/2018	Date: 8/16/2018	Date: 8/16/2018	<b>68031</b>																																		
					<b>Phone: 716-684-0001</b> <b>Fax: 716-684-0987</b> <b>E-Mail: info@pcb.com</b>																																				