Model Number HM	CABLE CONNECTOR							rision: NR N #: 43334
In the interest of constant produc	ENGLISH Circular Multi-conductor 6-pin Plug (male pin) Push-Pull Clamp -85 to +266 °F 0.47 in x 1.81 in 0.87 oz In temperature unless otherwise specified. Foduct improvement, we reserve the right to	Circular Multi-conductor 6-pin Plug (male pin) Push-Pull Clamp -65 to +130 °C 12.00 mm x 46.00 mm 24.66 gm change specifications without notice	[1] [1] [2] [2] ce.	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used. NOTES: [1]Additional cable strain relief sleeve/boot (material : TPE), with a temperature rating of -60 +100°C (-76°F to +212°F), is provided with cable models 003, 042, 062, and 097. [2]Typical.			used.	
ICP [®] is a registered trademark o	of PCB Group, Inc.			Entered: AP	Engineer: GD	Sales: BRS	Approved: BAM	Spec Number
				Date: 9/4/2014	Date: 9/4/2014	Date: 9/4/2014	Date: 9/4/2014	59874
					3 <i>PIEZOTI</i> enue, Depew, NY 1-		Fax: 716-6	6-684-0001 684-0987 50@pcb.com