Model Number <b>HX</b>	CABLE CONNECTOR						ision: A N#: 47806	
Performance Connector Style Connection Type Connection Type Coupling Method Coupling Thread Strain Relief Environmental	ENGLISH  Circular  Multi-conductor 5-pin  Plug (male pin)  Threaded  No English equivalent  Optional	SI Circular Multi-conductor 5-pin Plug (male pin) Threaded M12 x 1 Male Optional	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.					
Temperature Range Physical	-40 to +185 °F	-40 to +85 °C	Entered: LK	Engineer: RB	Sales: MC	Approved: BAM	Spec Number:	
ROHS Compliant	Yes	Yes	Lillered. LK	Liigineer. Kb	Sales. IVIC	Approved. BAIVI	Spec Number.	
Housing Material	PBT, Black .78 in x 2.4 in	PBT, Black 20 mm x 61 mm	Date: 8/27/2018	Date: 8/27/2018	Date: 8/27/2018	Date: 8/27/2018	59873	
Size (OD x Length) Weight	.70 IITX 2.4 III .83 oz	23.5 g			•	-1	•	
All specifications are at room temperature unless otherwise specified.  In the interest of constant product improvement, we reserve the right to change specifications without notice.  ICP® is a registered trademark of PCB Group, Inc.			PCB PIEZUTRUNICS			Fax: 716-6	Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com	