


Model Number NF	CABLE CONNECTOR		Revision: NR ECN #:	
Performance	ENGLISH	SI	OPTIONAL VERSIONS	
Connector Style	Triple Splice BNC	Triple Splice BNC	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.	
Connection Type	Plug (male pin)	Plug (male pin)		
Coupling Method	Bayonet	Bayonet		
Strain Relief	Heat Shrink	Heat Shrink		
Environmental				
Temperature Range	-40 to +176 °F	-40 to +80 °C		
Physical				
Electrical Connections(Red)	X axis	X axis	Entered: <i>JH</i>	Engineer: <i>nmn</i>
(Green)	Y axis	Y axis	Sales: <i>JH</i>	Approved: <i>EB</i>
(White)	Z axis	Z axis	Spec Number:	
(Black)	Shield	Shield	Date: <i>12-1-09</i>	Date: <i>12-1-09</i>
(Shield)	Shield	Shield	Date: <i>12-1-09</i>	Date: <i>12-3-09</i>
ROHS Compliant	No	No	 <p>IMI SENSORS A PCB PIEZOTRONICS DIV.</p> <p>IMI Sensors 3425 Walden Depew, NY 14043 UNITED STATES Phone: 800-959-4464 Fax: 716-684-3823 E-Mail: imi@pcb.com Web site: http://www.imi-sensors.com</p>	
Housing Material	Brass	Brass		
Finish	Nickel Coated	Nickel Coated		
Size (Length)	12 in	30.5 mm		
<p><i>All specifications are at room temperature unless otherwise specified.</i> <i>In the interest of constant product improvement, we reserve the right to change specifications without notice.</i></p>				