

Model Number
NU

CABLE CONNECTOR

Revision: NR
ECN #: 34842

Performance

Connector Style
Strain Relief

Physical

Electrical Connections(Red)
(Black)
(Orange)
(Blue)
(Green)
(Yellow)
(White)
(Gray)
(Solid Wire)

ROHS Compliant

*All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.*

ICP® is a registered trademark of PCB Group, Inc.

ENGLISH

Pigtail
Heat Shrink

Pos (+) Power
Ground
X axis Pos (+) Output
X Axis Neg (-) Output
Y axis Pos (+) Output
Y axis Neg (-) Output
Z axis Pos (+) Output
Z axis Neg (-) Output
Shield
No

SI

Pigtail
Heat Shrink

Pos (+) Power
Ground
X axis Pos (+) Output
X Axis Neg (-) Output
Y axis Pos (+) Output
Y axis Neg (-) Output
Z axis Pos (+) Output
Z axis Neg (-) Output
Shield
No

[1]

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

[1] Labeled for use with Series 3743 triax accelerometer.

Entered: <i>LH</i>	Engineer: <i>JK</i>	Sales: <i>AM</i>	Approved: <i>EB</i>	Spec Number:
Date: <i>1-25-11</i>	Date: <i>1-18-11</i>	Date: <i>1-18-11</i>	Date: <i>1-19-11</i>	49046



3425 Walden Avenue, Depew, NY 14043

Phone: 716-684-0001
Fax: 716-684-0987
E-Mail: electronics@pcb.com