


Model Number PB	<h1>CABLE CONNECTOR</h1>			Revision: NR ECN #: 37637					
Performance Connector Style Connector Style Connection Type Connection Type Coupling Method Coupling Thread Strain Relief	ENGLISH MIL-C-5015 Right Angle 2-socket Jack (female socket / recepticle) Threaded 5/8-24 female Molded Boot	SI MIL-C-5015 Right Angle 2-socket Jack (female socket / recepticle) Threaded 5/8-24 female Molded Boot	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.						
Environmental Temperature Range	-67 to +356 °F	-55 to +180 °C	<table border="1"> <tr> <td>Entered: DMW</td> <td>Engineer: JDK</td> <td>Sales: JJM</td> <td>Approved: BAM</td> <td>Spec Number:</td> </tr> </table>		Entered: DMW	Engineer: JDK	Sales: JJM	Approved: BAM	Spec Number:
Entered: DMW	Engineer: JDK	Sales: JJM	Approved: BAM	Spec Number:					
Physical Size (OD x Length x Height) Weight	0.75 in x 1.63 in x 1.50 in 0.65 oz	19.1 mm x 41.4 mm x 38.1 mm 18.4 gm	<table border="1"> <tr> <td>Date: 11/15/2011</td> <td>Date: 11/15/2011</td> <td>Date: 11/15/2011</td> <td>Date: 11/15/2011</td> <td style="text-align: center;">51509</td> </tr> </table>		Date: 11/15/2011	Date: 11/15/2011	Date: 11/15/2011	Date: 11/15/2011	51509
Date: 11/15/2011	Date: 11/15/2011	Date: 11/15/2011	Date: 11/15/2011	51509					
<i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i> ICP® is a registered trademark of PCB Group, Inc.			 <p> Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: electronics@pcb.com </p> <p>3425 Walden Avenue, Depew, NY 14043</p>						