


Model Number PD	CABLE CONNECTOR		Revision: NR ECN #: 35913	
Performance Connector Style Connection Type Coupling Method(Keyed) Strain Relief Environmental Temperature Range Physical Electrical Connections(Contact 1) (Contact 2) (Contact 3) Housing Material Size (Length x Height x Width) Weight	ENGLISH Multi-conductor Plug with Female Contact 3-socket Push On Clamp -67 to 221 °F White Black Red Nylon .57 in x .27 in x .30 in .032 oz	SI Multi-conductor Plug with Female Contact 3-socket Push On Clamp -55 to 105 °C White Black Red Nylon 14.5 mm x 6.9 mm x 7.62 mm .91 gm	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.	
<i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i>			Entered: <i>JH</i>	Engineer: <i>JK</i>
ICP® is a registered trademark of PCB Group, Inc.			Date: <i>5-27-11</i>	Date: <i>5-27-11</i>
			Date: <i>5-27-11</i>	Date: <i>5-26-11</i>
			Spec Number: 50420  PCB PIEZOTRONICS™ ELECTRONICS DIVISION 3425 Walden Avenue, Depew, NY 14043 Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: electronics@pcb.com	