Model Number PE	CABLE CONNECTOR			Revision: NR ECN #: 35913	
Performance Connector Style	<u>ENGLISH</u> BNC Circular	<u>SI</u> BNC Circular	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.		
Connection Type Coupling Method(Locking) Strain Relief Environmental	Plug (male pin) Bayonet Potted	Plug (male pin) Bayonet Potted			
Temperature Range Electrical Impedance	-40 to 221 °F 50 ohm	-40 to 105 °C 50 ohm			
Insulation Resistance Physical	5 Gohm	5 Gohm			
Electrical Connections(Center Pin) (Shell)	Signal/Power Ground	Signal/Power Ground	Entered: Lt Engineer: Sales: Approved:	Spec Number:	
Housing Material Finish Size (OD x Length)	Brass Nickel Coated .57 in x 1.1 in	Brass Nickel Coated 14 mm x 28 mm	Date: 5-27-11 Date: 5-27-11 Date: 5-21	50421	
Weight 0.51 oz 14 gm  All specifications are at room temperature unless otherwise specified.  In the interest of constant product improvement, we reserve the right to change specifications without notice.			Fax: 716-6	Phone: 716-684-0001 Fax: 716-684-0987	
ICP <sup>®</sup> is a registered trademark of PCB Group, Inc.			3425 Walden Avenue, Depew, NY 14043 E-Mail: ele	ctronics@pcb.com	