

	ENGLISH	SI
<b>Performance</b>		
Connector Style	Pigtail	Pigtail
Connector Style	BNC	BNC
Connection Type	Plug (male pin)	Plug (male pin)
Coupling Method	Bayonet	Bayonet
Strain Relief	Heat Shrink	Heat Shrink
<b>Environmental</b>		
Temperature Range	-67 to +230 °F	-55 to +110 °C
<b>Physical</b>		
Electrical Connections	"See Outline Drawing"	"See Outline Drawing"
ROHS Compliant	Yes	Yes

**OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

**NOTES:**

Entered: ND	Engineer: GD	Sales: BS	Approved: BAM	Spec Number:
Date: 04/06/2022	Date: 04/06/2022	Date: 04/06/2022	Date: 04/06/2022	51235

All specifications are at room temperature unless otherwise specified.  
 In the interest of constant product improvement, we reserve the right to change specifications without notice.

**PCB PIEZOTRONICS**  
AN AMPHENOL COMPANY

Phone: 716-684-0001  
 Fax: 716-684-0987  
 E-Mail: [info@pcb.com](mailto:info@pcb.com)

3425 Walden Avenue, Depew, NY 14043