Model Number QX	CABLE CONNECTOR					_	rision: NR N #: 47854
Performance Connector Style Connection Type Coupling Method Coupling Thread Strain Relief Environmental Temperature Range Physical	ENGLISH Coaxial Plug (male pin) Threaded 10-32 female Molded Boot -320 to 500 °F	SI Coaxial Plug (male pin) Threaded 10-32 female Molded Boot -196 to 260 °C	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.				
ROHS Compliant Mounting Torque	Yes 15 to 20 in-oz	Yes 11 to 15 N-cm	Entered: LK	Engineer: RB	Sales: KK	Approved: BAM	Spec Number:
Size (Hex x Length) Weight	0.25 in x 0.94 in 0.1 oz	6.4 mm x 24 mm 2 gm	Date: 2/16/2018	Date: 2/16/2018	Date: 2/16/2018	Date: 2/16/2018	68835
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice. ICP <sup>®</sup> is a registered trademark of PCB Group, Inc.		<b>PCB</b> PIEZOTRONICS		Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com			