


PCB Load & Torque Inc. claims proprietary rights in the information disclosed hereon. Neither it nor any reproduction thereof will be disclosed to others without the written consent of PCB Load and Torque Inc.

REVISIONS		
REV	DESCRIPTION	ECO
NR	RELEASED TO DRAFTING	36164

46139

4 CONDUCTOR BLACK SHIELDED CABLE 10.0 FT [3.0 M] LONG TERMINATING IN PIGTAILS

STRAIN RELIEF



3.50 [88.9]

2.50 [63.5]

2X 5/8-18 UNF - 2B THRU ONE WALL

Ø.65 [16.5]

.75 [19.1]

1.50 [38.1]

1.61 [41.0]

2.00 [50.8]

1.25 [31.8]

2.55 [64.8]

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE:

DIMENSIONS IN INCHES

DIMENSIONS IN MILLIMETERS [IN BRACKETS]

DECIMALS XX ±.01
XXX ±.005

DECIMALS X ± 0.3
XX ± 0.13

ANGLES ± .5 DEGREES

ANGLES ± .5 DEGREES

FILLETS AND RADII
.015 MAX

FILLETS AND RADII
0.38 MAX

DRAWN

CHECKED

ENGINEER

SMB	06.29.11	JM	06.29.11	JAM	6/29/11
-----	----------	----	----------	-----	---------

TITLE
OUTLINE DRAWING
MODEL 1631-06C
S-CELL

PCB LOAD & TORQUE
A PCB GROUP COMPANY

24350 Indoplex Circle, Farmington Hills, MI 48335
(716) 684-0001 E-MAIL: linfo@pcbloadtorque.com

DWG. NO.

46139

SCALE: FULL SHEET 1 OF 1