


Model Number 1102-04A		STRAIN GAGE LOAD CELL		Revision: H ECN #: 43815										
Performance	ENGLISH	SI		OPTIONAL VERSIONS										
Measurement Range	300 lb	1334 N	[5]	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.										
Sensitivity(± 10 %)	2 mV/V	2 mV/V	[6]											
Non-Linearity	≤ 0.05 % FS	≤ 0.05 % FS												
Hysteresis	≤ 0.05 % FS	≤ 0.05 % FS												
Non-Repeatability	≤ 0.02 % FS	≤ 0.02 % FS												
Eccentric Load Sensitivity	≤ .25 %/in	≤ .25 %/25.4mm												
Resonant Frequency	7.0 kHz	7.0 kHz												
Creep(in 20 minutes)	≤ .025 %	≤ .025 %												
Static Error Band	≤ .05 % FS	≤ .05 % FS												
Environmental					NOTES:									
Overload Limit	450 lb	2000 N		[1]Nominal.										
Load Limit(Side Force, F _X or F _Y)	300 lb	1334 N	[3]	[2]Calibrated at 10 VDC, usable 5 to 20 VDC or VAC RMS.										
Load Limit(Bending Moment, M _X or M _Y)	300 in-lb	34 Nm	[3]	[3]Singularly applied, i.e. no other extraneous loads.										
Load Limit(Axial Torque, M _Z)	65 in-lb	7 Nm	[3]	[4]Over compensated operating temperature range.										
Temperature Range(Operating)	-65 to +200 °F	-54 to +93 °C		[5]FS - Full Scale.										
Temperature Range(Compensated)	+70 to +170 °F	+21 to +77 °C		[6]RO - Rated Output.										
Temperature Effect on Output(Maximum)	± 0.0015 %Reading/°F	± 0.0027 %Reading/°C	[4]	[7]See Outline Drawing 51277 for Complete Dimensions										
Temperature Effect on Zero Balance(Maximum)	± 0.0008 %FS/°F	± 0.0015 %FS/°C	[4]	OPTIONAL ACCESSORIES:										
Electrical				Model 181-012A PT06A-10-6S(SR)										
Bridge Resistance	700 Ohm	700 Ohm	[1]	Model 8311-01-10A CABLE										
Excitation Voltage(Recommended)	10 VDC	10 VDC	[2]											
Insulation Resistance	>5x10 ⁹ Ohm	>5x10 ⁹ Ohm												
Zero Balance	≤ 1 % FS	≤ 1 % FS												
Output Polarity	+Tension	+Tension												
Physical														
Size (Diameter x Height)	2.75 in x 1.5 in	69.9 mm x 38.1 mm	[7]											
Weight	0.67 lb	304 g												
Mounting Thread	1/4-28 Female	No Metric Equivalent												
Housing Material	Painted Aluminum	Painted Aluminum												
Sensing Element	Strain Gage	Strain Gage												
Deflection at Full Scale Capacity	0.003 in	0.08 mm												
Electrical Connector	PT02E-10-6P	PT02E-10-6P												
<i>All specifications are at room temperature unless otherwise specified.</i>														
<i>In the interest of constant product improvement, we reserve the right to change specifications without notice.</i>														
<table border="1" style="width: 100%;"> <tr> <td>Entered: AP</td> <td>Engineer: PE</td> <td>Sales: JC</td> <td>Approved: JSD</td> <td>Spec Number:</td> </tr> <tr> <td>Date: 2/17/2015</td> <td>Date: 2/17/2015</td> <td>Date: 2/17/2015</td> <td>Date: 2/17/2015</td> <td style="text-align: center;">18330</td> </tr> </table>					Entered: AP	Engineer: PE	Sales: JC	Approved: JSD	Spec Number:	Date: 2/17/2015	Date: 2/17/2015	Date: 2/17/2015	Date: 2/17/2015	18330
Entered: AP	Engineer: PE	Sales: JC	Approved: JSD	Spec Number:										
Date: 2/17/2015	Date: 2/17/2015	Date: 2/17/2015	Date: 2/17/2015	18330										
 <p>PCB Load & Torque, Inc. 24350 Indoplex Circle Farmington Hills, MI 48335 UNITED STATES Phone: 866-684-7107 Fax: 716-684-0987 E-Mail: linfo@pcbloadtorque.com Web site: http://www.pcbloadtorque.com</p>														