

Model Number
66212ANZ1

ICP® TO-5 ACCELEROMETER

Revision: A
ECN #: 35587

Performance

	ENGLISH	SI	
Sensitivity(± 20 %)	100 mV/g	1.02 mV/(m/s ²)	[2]
Measurement Range	± 50 g	± 490 m/s ²	[3]
Frequency Range(± 3 dB)	30 to 60,000 cpm	0.5 to 10,000 Hz	[4][5]
Resonant Frequency	1500 kcpm	25 kHz	[1][5]
Broadband Resolution(1 to 10,000 Hz)	350 µg rms	3434 µm/sec ² rms	[1]
Non-Linearity	≤ 1 %	≤ 1 %	[6]
Transverse Sensitivity	≤ 7 %	≤ 7 %	

Environmental


Overload Limit(Shock)	5000 g pk	49,000 m/s ² pk	
Temperature Range(Operating)	-65 to +185 °F	-54 to +85 °C	
Temperature Response	See Graph	See Graph	[1]

Electrical

Settling Time(within 1% of bias)	≤ 2 sec	≤ 2 sec	
Discharge Time Constant	0.3 sec	0.3 sec	
Excitation Voltage	18 to 28 VDC	18 to 28 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Impedance	<150 ohm	<150 ohm	
Output Bias Voltage	8 to 12 VDC	8 to 12 VDC	
Spectral Noise(10 Hz)	8 µg/√Hz	78.5 (µm/sec ²)/√Hz	[1]
Spectral Noise(100 Hz)	5 µg/√Hz	49.1 (µm/sec ²)/√Hz	[1]
Spectral Noise(1 kHz)	4 µg/√Hz	39.2 (µm/sec ²)/√Hz	[1]

Physical

Size (Lip Diameter x Height)	0.36 in x 0.38 in	9.1 mm x 9.7 mm	
Weight	0.1 oz	3 gm	
Mounting	Adhesive/Solder	Adhesive/Solder	
Sensing Element	Ceramic	Ceramic	
Sensing Geometry	Shear	Shear	
Housing Material	Stainless Steel	Stainless Steel	
Sealing	Welded Hermetic	Welded Hermetic	
Electrical Connector	Header Pins	Header Pins	
Electrical Connection Position	Bottom	Bottom	
Electrical Connections(Pin 1)	Signal / Power	Signal / Power	
Electrical Connections(Pin 2)	Ground	Ground	
Electrical Connections(Pin 3)	Not Used	Not Used	



OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

HT - High temperature, extends normal operation temperatures
Temperature Range(Operating) -65 to 250 °F -54 to +121 °C

RH - RoHS Compliant

NOTES:

- [1] Typical.
- [2] Conversion Factor 1g = 9.81 m/s².
- [3] Negative output in upward direction when pin mounted.
- [4] The high frequency tolerance is accurate within ±10% of the specified frequency.
- [5] Performance depends on mounting
- [6] Zero-based, least-squares, straight line method.
- [7] See PCB Declaration of Conformance PS023 or PS060 for details.

SUPPLIED ACCESSORIES:

Model ICS-2 NIST-traceable single-axis single-point amplitude response calibration at 6000 cpm (100 Hz) (1)

Entered: omw	Engineer: DJD	Sales: SAC	Approved: BAM	Spec Number:
Date: 4/21/11	Date: 4/21/11	Date: 4/21/11	Date: 4/21/11	46761

All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.

ICP® is a registered trademark of PCB Group, Inc.

IMI SENSORS
A PCB PIEZOTRONICS DIV.
3425 Walden Avenue, Depew, NY 14043

Phone: 800-959-4464
Fax: 716-684-3823
E-Mail: imi@pcb.com