

Model Number
685A09

MECHANICAL VIBRATION SWITCH

Revision: E
ECN #: 55476

Performance

Measurement Range
Frequency Range
Relay
Relay(Contacts)(DPDT)

ENGLISH

7 g pk
0 to 6,000 cpm
3A Form C 480 VAC
Normally Open / Closed

SI

68.7 m/s² pk
0 to 100 Hz
3A Form C 480 VAC
Normally Open / Closed

Control Interface

Reset Function

Momentary Pushbutton
Switch

Momentary Pushbutton
Switch

Environmental

Temperature Range(Operating)
Enclosure Rating

-40 to 140 °F
IP66

-40 to 60 °C
IP66

Physical

Size (Width x Height x Depth)

4.35 in x 3.30 in x 4.35 in

110.5 mm x 83.8 mm x 110.5 mm

Weight

2.5 lb

1,132 gm

Sensing Element

Magnet

Magnet

Housing Material

Aluminum Alloy

Aluminum Alloy

Electrical Connector

Screw Terminals

Screw Terminals

Screw Terminal Wire Size

24-14 AWG

0.2 - 2.5 mm²

Cable Input

3/4-14 NPT

3/4-14 NPT

Mounting Hole Size

0.25 in

6.4 mm

Sensing Geometry

Inertial Element

Inertial Element

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

[1]PS206 Declaration of Conformity PS206



All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.

Entered: ND	Engineer: NJF	Sales: JL	Approved: NJF	Spec Number:
Date: 02/10/2025	Date: 02/10/2025	Date: 02/10/2025	Date: 02/10/2025	50857



Phone: 800-959-4464
Fax: 716-684-3823
E-Mail: imi@pcb.com

3425 Walden Avenue, Depew, NY 14043