

	ENGLISH	SI
Performance		
Channels	36	36
Environmental		
Enclosure Rating	Nema 4X	IP66
Physical		
Electrical Connector(Output, Vibration)	BNC Jack	BNC Jack
Electrical Connector(Output, Temperature)	BNC Jack	BNC Jack
Electrical Connector(Output, Vibration)	2-Pin Mil	2-Pin Mil
Electrical Connector(Input)	Terminal Block	Terminal Block
Electrical Connector(Output, Vibration)	Terminal Block	Terminal Block
Housing Material	Fiberglass	Fiberglass
Size (Height x Width x Depth)	20.6 in x 16.6 in x 7.9 in	523.2 mm x 421.6 mm x 200.6 mm
Weight	25.9 lb	11.7 kg

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

691050 - 36 Individual Cord Grips, PGME07

691054 - 3 Individual Cord Grips, PGME21

691055 - 3 Conduit Fittings, 1.5 Inch.

691056 - 6 Conduit Fittings, 1.5 Inch.

691057 - 6 Individual cord grips, PGME21

691058 - 36 Individual cord grips, PGME07 and 3 individual cord grips, PGME21

NOTES:
[1]See PCB Declaration of Conformance PS174 for details.

SUPPLIED ACCESSORIES:
Model 080A192 4-socket terminal block (3)



Entered: LK	Engineer: gs	Sales: MC	Approved: BAM	Spec Number:
Date: 08/26/2020	Date: 08/26/2020	Date: 08/26/2020	Date: 08/26/2020	70852

All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.
ICP® is a registered trademark of PCB Piezotronics, Inc.

Phone: 800-959-4464
Fax: 716-684-3823
E-Mail: imi@pcb.com

3425 Walden Avenue, Depew, NY 14043