Model Number 106B50	ICP® PRESSURE SENSOR	Revision: N ECN #: 54898

Performance	ENGLISH	SI	
Measurement Range(for ±2.5V output)	5 psi	34.45 kPa	
Sensitivity(± 15 %)	500 mV/psi	72.5 mV/kPa	
Maximum Pressure(step)	100 psi	690 kPa	
Maximum Pressure(static)	500 psi	3,448 kPa	
Resolution	0.07 mpsi	0.00048 kPa	[1]
Resonant Frequency	≥ 40 kHz	≥ 40 kHz	
Rise Time	≤ 12 µ sec	≤ 12 µ sec	
Low Frequency Response(- 5 %)	0.5 Hz	0.5 Hz	
Non-Linearity	≤ 1 % FS	≤ 1 % FS	[2]
Environmental			
Acceleration Sensitivity	0.002 psi/g	0.0014 kPa/(m/s²)	[1]
Temperature Range(Operating)	-65 to +250 °F	-54 to +121 °C	
Temperature Coefficient of Sensitivity	≤ 0.03 %/°F	≤ 0.054 %/°C	
Maximum Flash Temperature	3,000 °F	1,649 °C	
Maximum Vibration	500 g pk	4,900 m/s² pk	
Maximum Shock	1,000 g pk	9,800 m/s² pk	
Electrical			
Output Polarity(Positive Pressure)	Positive	Positive	
Discharge Time Constant(at room temp)	≥ 1 sec	≥ 1 sec	
Excitation Voltage	11 to 30 VDC	11 to 30 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Impedance	≤ 100 Ohm	≤ 100 Ohm	
Output Bias Voltage	3 to 8 VDC	3 to 8 VDC	
Physical			
Sensing Element	Quartz	Quartz	
Housing Material	17-4 Stainless Steel	17-4 Stainless Steel	
Diaphragm	316L Stainless Steel	316L Stainless Steel	
Sealing	Welded Hermetic	Welded Hermetic	
Electrical Connector	10-32 Coaxial Jack	10-32 Coaxial Jack	
Weight	1.13 oz	32 gm	

CE

UK CA [3]

All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.
ICP® is a registered trademark of PCB Piezotronics, Inc.

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

E - Emralon coating			
Coating	Emralon	Emralon	
Electrical Isolation	10^8 Ohm	10^8 Ohm	[4]
J - Ground Isolated			
Electrical Isolation(50 V)	10^8 Ohm	10^8 Ohm	[5]

W - Water Resistant Cable
Supplied Accessory: Model 060A11 Acetal clamp nut 3/4-16-2A thd 3/4" hex (1) [5]

WM - Water Resistant Cable
Supplied Accessory: Model 060A13 Metric Acetal clamp nut M20 x 1.5-6g thd 20 mm hex (1)

NOTES:

[1]Typical.
[2]Zero-based, least-squares, straight line method.
[3]See PCB Declaration of Conformance PS023 for details.
[4]Used with optional mounting adaptor.
[5]Clamp nut installed prior to cable attachment

SUPPLIED ACCESSORIES:

Model 060A11 Acetal clamp nut 3/4-16-2A thd 3/4" hex (1)
Model 060A13 Metric Acetal clamp nut M20 x 1.5-6g thd 20 mm hex (1)
Model 065A36 Seal, .687" OD x .625" ID x .060", Derlin (3)
Model PCS-1 Calibration of dynamic pressure sensors at 100% full scale, max 15 kpsi range.
Model PCS-17 Electrostatic Actuator (ESA) frequency response from 20 Hz to 50 kHz
Model PCS-24 Sensor sensitivity calibration with Pistonphone

Entered: ND	Engineer: AJA	Sales: MV	Approved: RPF	Spec Number:
Date: 05/29/2024	Date: 05/29/2024	Date: 05/29/2024	Date: 05/29/2024	106-2500-80

PCB PIEZOTRONICS
AN AMPHENOL COMPANY
Phone: 716-684-0001
Fax: 716-684-0987
E-Mail: info@pcb.com
3425 Walden Avenue, Depew, NY 14043