



MODEL 378A06

1/2" FREE-FIELD MICROPHONE & PREAMPLIFIER

- Frequency: 3.15 Hz - 40 kHz (± 3 dB)
- Max amplitude: 150 dB (3% distortion)
- Inherent noise: 22 dB(A)

TYPICAL APPLICATIONS

- Environmental monitoring
- Railway and horn testing
- Sonic boom measurements

STANDARDS COMPLIANCE

- IEC 61094-4 WS2F compliant, and designed to be used in an IEC 61672 Class 1 compliant system for sound level meter use
- Calibration reference microphone traceable to NIST, PTB or DFM National Labs
- PCB calibration service accredited to ISO 17025, ANSI-Z540.3 by A2LA or ILAC



USE OF MODEL 378A06

Model 378A06 is a 1/2 in (12 mm) prepolarized microphone and preamplifier combination for applications where high frequencies (up to 40 kHz) need to be measured accurately. As an alternative to a high sensitivity microphone, it has an enhanced upper dynamic range (150 dB) which minimizes overloading. Previously, these applications required a 1/4" microphone system which is both higher in price and inherent noise than the 378A06 system.


Acoustic pressure waves may be altered by objects in the sound field including the microphone itself. The 378A06 corrects for its own presence, providing more accurate measurements within a free-field.

POLARIZATION VOLTAGE – ICP® (0V) PREPOLARIZED

PCB® is the inventor of ICP® sensor power technology. All manufacturers of IEC 61094-4 compliant prepolarized (0V) microphones use the technology that PCB developed. Prepolarized microphones operate on 2-20 mA constant current supply and use coaxial cables resulting in significant per channel cost savings over the PCB 200V models. Other ICP® compatible sensors such as accelerometers, force, strain, and pressure sensors use the same power supplies and cables as prepolarized microphones, further reducing set-up time and initial investment costs.

PCB® QUALITY COMMITMENT

PCB is uniquely equipped with a state of the art, CNC machining facility, allowing control over quality, pricing, and delivery. Investments in clean rooms, anechoic, and environmental test chambers, combined with our rigorous testing and aging process, ensures our products will survive in demanding environmental conditions. PCB has the industry's best 5-year warranty with a "Total Customer Satisfaction" policy.



378A06 PREPOLARIZED FREE-FIELD MICROPHONE SYSTEM		
Nominal Microphone Diameter	in (mm)	1/2 (12)
Sensitivity at 250 Hz (± 2 dB)	mV/Pa (dB re 1 V/Pa)	12.6 (-38)
Frequency Range (± 3 dB)	Hz	3.15 - 40,000
Frequency Range (± 2 dB)	Hz	3.15 - 31,500
Cartridge Thermal Noise (Microphone)	dB[A] re 20 µPa	20
Inherent Noise with 426E01 Preamp	dB[A] re 20 µPa	22
Harmonic Distortion Limit: 3%	dB re 20 µPa	162
Distortion Limit with 426E01 Preamp	dB re 20 µPa	150
Environmental Specifications		
Operating Temperature Range Microphone	°F (°C)	-40 to +248 (-40 to +120)
Operating Temp. with 426E01 Preamp	°F (°C)	-40 to +176 (-40 to +80)
Operating Temp. with HT426E01 Preamp	°F (°C)	-40 to +248 (-40 to +120)
Electrical & Physical Specifications		
Polarization Voltage	V	0
Constant Current Excitation	mA	2 - 20
Size (Diameter x Length with Grid)	in (mm)	0.52 x 3.47 (12.7 x 87.8)
Connector	Coaxial	BNC Jack

* all specifications typical unless otherwise noted

OPTIONAL ACCESSORIES

- **079A06** – 1/2" microphone windscreen
- **079A11** – 1/2" microphone holder
- **079A15** – tripod microphone stand with boom arm
- **079B16** – miniature microphone stand
- **079A18** – clamp on flexible extension arm
- **079B21** – 1/2" nose cone
- **079C23** – microphone holder with swivel mount
- **079A42** – 1/2" right angle adapter
- **079A44** – extension arm for flexible clamp
- **CAL200** – handheld calibrator
- **ACS-63** – microphone system calibration



3425 Walden Avenue, Depew, NY 14043-2495 USA
 Toll-Free in the USA: 800 828 8840
 Phone: 1 716 684 0001 | Email: info@pcb.com

PCB Piezotronics, Inc. is a designer and manufacturer of microphones, vibration, pressure, force, torque, load, and strain sensors, as well as the pioneer of ICP® technology used by design engineers and predictive maintenance professionals worldwide for test, measurement, monitoring, and control requirements in automotive, aerospace, industrial, R&D, military, educational, commercial, OEM applications, and more. With a worldwide customer support team, 24-hour SensorLineSM, and a global distribution network, PCB® is committed to Total Customer Satisfaction. Visit www.pcb.com for more information. PCB Piezotronics, Inc. is a wholly owned subsidiary of MTS Systems Corporation. Additional information on MTS can be found at www.mts.com.

© 2019 PCB Piezotronics, Inc. In the interest of constant product improvement, specifications are subject to change without notice. PCB®, ICP®, Swiveler®, Modally Tuned®, and IMI® with associated logo are registered trademarks of PCB Piezotronics, Inc. in the United States. ICP® is a registered trademark of PCB Piezotronics Europe GmbH in Germany and other countries. UHT-12™ is a trademark of PCB Piezotronics, Inc. SensorLineSM is a service mark of PCB Piezotronics, Inc. SWIFT® is a registered trademark of MTS Systems Corporation in the United States.

TM-AC-378A06-0319



MTS Sensors, a division of MTS Systems Corporation (NASDAQ: MTSC), vastly expanded its range of products and solutions after MTS acquired PCB Piezotronics, Inc. in July, 2016. PCB Piezotronics, Inc. is a wholly owned subsidiary of MTS Systems Corp.; IMI Sensors and Larson Davis are divisions of PCB Piezotronics, Inc.; Accumetrics, Inc. and The Modal Shop, Inc. are subsidiaries of PCB Piezotronics, Inc.