

Model Number <b>055BP050BZ</b>	<b>HIGH-TEMP PTFE HEAVY DUTY CABLE ASSEMBLY</b>		Revision NR ECN #:
<b>Performance</b> Cable Style  Number of Conductors Connector Model (sensor side) Connector Style (sensor side) Connection Type (sensor side) Coupling Method (sensor side) Connector Style (termination)	<b>ENGLISH</b> Multi Conductor - Shielded  2  Aluminum MIL-C-5015 2-pin Threaded Blunt Cut	<b>SI</b> Multi Conductor - Shielded  2  Aluminum MIL-C-5015 2-pin Threaded Blunt Cut	<b>Optional Versions</b> (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)
<b>Environmental</b> Temperature Range	-65 to 325 °F	-55 to 163 °C	
<b>Electrical</b> Capacitance	27 pF/ft	89 pF/m	
<b>Physical</b> Cable Jacket Diameter Cable Jacket Material Cable Jacket Color Conductor Style  Conductor Material Conductor Diameter (20 AWG) Shield Type Over Bundle  Shield Material Over Bundle Bend Radius (minimum) Weight	0.19 in PTFE Orange Stranded - 19 strands 32 AWG Tin Plated Copper 0.038 in Braid: 85% Minimum Coverage Tin Plated Copper 1.9 in 0.52 oz/ft	4.83 mm PTFE Orange Stranded - 19 strands 32 AWG Tin Plated Copper 0.965 mm Braid: 85% Minimum Coverage Tin Plated Copper 48.3 mm 47.97 gm/m	
<p><i>All specifications are at room temperature unless otherwise specified.</i></p> <p>In the interest of constant product improvement, we reserve the right to change specifications without notice.</p>			
Entered: ECB Date: 10/06/2011	Engineer: MJN Date: 10/06/2011	Sales: MRS Date: 10/06/2011	Approved: MRS Date: 10/06/2011 Spec Number: <b>N/A</b>
		3425 Walden Avenue Depew, NY 14043 UNITED STATES Phone: 800-828-8840 Fax: 716-684-0987 E-mail: info@pcb.com Web site: www.pcb.com	