


Model Number CE	CE - 2 PIN MIL 3103 W/STRAIN RELIEF			Revision: A ECN #: 48326																																					
<table border="0"> <thead> <tr> <th data-bbox="142 215 472 243">Performance</th> <th data-bbox="472 215 766 243"><u>ENGLISH</u></th> <th data-bbox="766 215 1119 243"><u>SI</u></th> </tr> </thead> <tbody> <tr> <td>Connector Style</td> <td>3101A</td> <td>3101A</td> </tr> <tr> <td>Connection Type</td> <td>2-pin</td> <td>2-pin</td> </tr> <tr> <td>Coupling Method</td> <td>Threaded</td> <td>Threaded</td> </tr> <tr> <td>Coupling Thread</td> <td>5/8-24 male</td> <td>5/8-24 male</td> </tr> <tr> <td>Strain Relief</td> <td>Clamp</td> <td>Clamp</td> </tr> <tr> <td colspan="3">Environmental</td> </tr> <tr> <td>Temperature Range</td> <td>-67 to +257 °F</td> <td>-55 to +125 °C</td> </tr> <tr> <td colspan="3">Physical</td> </tr> <tr> <td>ROHS Compliant</td> <td>Yes</td> <td>Yes</td> </tr> <tr> <td>Size (OD x Length x Width)</td> <td>0.75 in x 1.88 in x 0.88 in</td> <td>19.05 mm x 47.75 mm x 22.35 mm</td> </tr> <tr> <td>Weight</td> <td>1.21 oz</td> <td>34.18 gm</td> </tr> </tbody> </table> <p data-bbox="142 527 1119 552"><i>All specifications are at room temperature unless otherwise specified.</i></p> <p data-bbox="142 552 1119 576"><i>In the interest of constant product improvement, we reserve the right to change specifications without notice.</i></p> <p data-bbox="142 576 1119 600">ICP® is a registered trademark of PCB Group, Inc.</p>			Performance	<u>ENGLISH</u>	<u>SI</u>	Connector Style	3101A	3101A	Connection Type	2-pin	2-pin	Coupling Method	Threaded	Threaded	Coupling Thread	5/8-24 male	5/8-24 male	Strain Relief	Clamp	Clamp	Environmental			Temperature Range	-67 to +257 °F	-55 to +125 °C	Physical			ROHS Compliant	Yes	Yes	Size (OD x Length x Width)	0.75 in x 1.88 in x 0.88 in	19.05 mm x 47.75 mm x 22.35 mm	Weight	1.21 oz	34.18 gm	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.		
Performance	<u>ENGLISH</u>	<u>SI</u>																																							
Connector Style	3101A	3101A																																							
Connection Type	2-pin	2-pin																																							
Coupling Method	Threaded	Threaded																																							
Coupling Thread	5/8-24 male	5/8-24 male																																							
Strain Relief	Clamp	Clamp																																							
Environmental																																									
Temperature Range	-67 to +257 °F	-55 to +125 °C																																							
Physical																																									
ROHS Compliant	Yes	Yes																																							
Size (OD x Length x Width)	0.75 in x 1.88 in x 0.88 in	19.05 mm x 47.75 mm x 22.35 mm																																							
Weight	1.21 oz	34.18 gm																																							
			Entered: LK	Engineer: RB	Sales: MC	Approved: BAM	Spec Number:																																		
			Date: 8/20/2018	Date: 8/20/2018	Date: 8/20/2018	Date: 8/20/2018	32565																																		
					Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com																																				