


Model Number DN	CABLE CONNECTOR		Revision NR ECN #:								
Performance Connector Style Connector Style Connection Type Connection Type Coupling Method Coupling Thread Environmental Temperature Range Physical Size (OD x Length) Weight	ENGLISH MIL-C-5015 Multi-conductor 2-socket Jack (female socket / receptacle) Threaded 5/8-24 female -67 to +250 °F 0.825 in x 1.73 in 0.39 oz	SI MIL-C-5015 Multi-conductor 2-socket Jack (female socket / recepticle) Threaded 5/8-24 female -55 to +121 °C 20.955 mm x 43.94 mm 11.04	Optional Versions (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)								
<p><i>All specifications are at room temperature unless otherwise specified.</i></p> <p>In the interest of constant product improvement, we reserve the right to change specifications without notice.</p> <p>ICP® is a registered trademark of PCB group, Inc.</p>											
<table border="1"> <tr> <td>Entered: DMP</td> <td>Engineer: MFG</td> <td>Sales: NJF</td> <td>Spec Number:</td> </tr> <tr> <td>Date: 11/28/2005</td> <td>Date: 11/28/2005</td> <td>Date: 11/28/2005</td> <td>32476</td> </tr> </table>				Entered: DMP	Engineer: MFG	Sales: NJF	Spec Number:	Date: 11/28/2005	Date: 11/28/2005	Date: 11/28/2005	32476
Entered: DMP	Engineer: MFG	Sales: NJF	Spec Number:								
Date: 11/28/2005	Date: 11/28/2005	Date: 11/28/2005	32476								
		Company: IMI Sensors Address: 3425 Walden Depew, NY 14043 UNITED STATES Phone: 800-959-4464 Fax: 716-684-3823 E-mail: imi@pcb.com Web site: http://www.imi-sensors.com									

