

Performance	ENGLISH	SI	
Sensitivity(± 20 %)(z axis)	0.25 mV/lb	0.06 mV/N	[1]
Sensitivity(± 20 %)(x or y axis)	1.25 mV/lb	0.28 mV/N	[1]
Measurement Range(z axis)	10,000 lb	44.48 kN	
Measurement Range(x or y axis)	4000 lb	17.79 kN	
Maximum Force(z axis)	11,000 lb	48.93 kN	
Maximum Force(x or y axis)	4400 lb	19.57 kN	
Maximum Moment(z axis)	240 ft-lb	325.4 Nm	
Maximum Moment(x or y axis)	325 ft-lb	440.7 Nm	
Broadband Resolution(x or y axis)	0.05 lb-rms	0.222 N-rms	[2]
Broadband Resolution(x or y axis)	0.01 lb-rms	0.04 N-rms	[2]
Upper Frequency Limit	10,000 Hz	10,000 Hz	
Low Frequency Response(-5 %)(z-axis)	0.01 Hz	0.01 Hz	
Low Frequency Response(-5 %)(x or y axis)	0.001 Hz	0.001 Hz	
Non-Linearity	≤ 1 % FS	≤ 1 % FS	[3]
Cross Talk(between x and y axis)	± 3 %	± 3 %	
Cross Talk(between (x or y axis) and z axis)	± 5 %	± 5 %	
Environmental			
Temperature Range	-65 to +250 °F	-54 to +121 °C	
Electrical			
Full Scale Output(Z Direction)	± 2.5 VDC	± 2.5 VDC	
Full Scale Output(X and Y Direction)	± 5 VDC	± 5 VDC	
Discharge Time Constant(z axis)	≥ 50 sec	≥ 50 sec	
Discharge Time Constant(x or y axis)	≥ 500 sec	≥ 500 sec	
Excitation Voltage(all channels)	20 to 30 VDC	20 to 30 VDC	
Constant Current Excitation(all channels)	2 to 20 mA	2 to 20 mA	
Output Impedance	≤ 100 Ohm	≤ 100 Ohm	
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC	
Spectral Noise(1 Hz)(X & Y)	0.003 lb/√Hz	0.0134 N/√Hz	
Spectral Noise(10 Hz)(X & Y)	0.001 lb/√Hz	0.00445 N/√Hz	
Spectral Noise(100 Hz)(X & Y)	0.0004 lb/√Hz	0.00178 N/√Hz	
Spectral Noise(1000 Hz)(X & Y)	0.0001 lb/√Hz	0.000445 N/√Hz	
Spectral Noise(1 Hz)(Z)	0.02 lb/√Hz	0.089 N/√Hz	
Spectral Noise(10 Hz)(Z)	0.005 lb/√Hz	0.0222 N/√Hz	
Spectral Noise(100 Hz)(Z)	0.002 lb/√Hz	0.0089 N/√Hz	
Spectral Noise(1000 Hz)(Z)	0.0005 lb/√Hz	0.00222 N/√Hz	
Output Polarity	Positive	Positive	
Physical			
Stiffness(z axis)	19.4 lb/μin	3.4 kN/μm	[2]
Stiffness(x or y axis)	5.7 lb/μin	1.0 kN/μm	[2]
Size (Height x Length x Width)	3.54 in x 3.15 in x 3.15 in	89.9 mm x 80.0 mm x 80.0 mm	
Weight	96.25 oz	2994 gm	
Housing Material	Stainless Steel	Stainless Steel	
Sealing	Hermetic	Hermetic	
Electrical Connector	4-Pin	4-Pin	
Electrical Connection Position	Side	Side	

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

M - Metric Mount

W - Water Resistant Cable

Electrical Connection Position Side Side

NOTES:

[1]Sensitivites are for listed preload. Sensitivites may vary ±5% depending on preload used.

[2]Typical.

[3]Zero-based, least-squares, straight line method.

[4]See PCB Declaration of Conformance PS023 for details.

--	--	--	--

Entered: LK	Engineer: BAM	Sales: RWM	Approved: BAM	Spec Number:
Date: 10/14/2015	Date: 10/14/2015	Date: 10/14/2015	Date: 10/14/2015	28787



[4]

All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.
 ICP® is a registered trademark of PCB Group, Inc.



Phone: 716-684-0001
 Fax: 716-684-0987
 E-Mail: info@pcb.com