

	ENGLISH	SI	
Performance			
Sensitivity(± 15 %)	0.28 pC/psi	0.041 pC/kPa	
Measurement Range	15 kpsi	103,400 kPa	
Maximum Pressure	35 kpsi	241,000 kPa	[1]
Resonant Frequency	≥ 175 kHz	≥ 175 kHz	
Rise Time(Reflected)	≤ 2.5 μ sec	≤ 2.5 μ sec	
Non-Linearity	≤ .5 % FS	≤ .5 % FS	[2]
Environmental			
Acceleration Sensitivity	0.03 psi/g	0.021 kPa/(m/s ²)	[3]
Temperature Range(Operating)	-50 to +325 °F	-46 to +163 °C	
Temperature Coefficient of Sensitivity	≤ 0.06 %/°F	≤ 0.108 %/°C	
Maximum Flash Temperature	3,000 °F	1,649 °C	
Maximum Vibration	2,000 g pk	19,600 m/s ² pk	
Maximum Shock	20,000 g pk	196,000 m/s ² pk	
Electrical			
Output Polarity(Positive Pressure)	Negative	Negative	
Capacitance	5 pF	5 pF	[3]
Insulation Resistance	≥ 10 ¹² Ohm	≥ 10 ¹² Ohm	
Physical			
Sensing Element	Quartz	Quartz	
Housing Material	Stainless Steel	Stainless Steel	
Diaphragm	Stainless Steel	Stainless Steel	
Sealing	Epoxy	Epoxy	
Electrical Connector	10-32 Coaxial Jack	10-32 Coaxial Jack	
Weight	0.52 oz	14.6 gm	

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

M - Metric Mount

P - Positive Output Polarity

W - Water Resistant Cable

NOTES:

[1]Non-Linearity for maximum pressure will be ≤ 2.0%

[2]Zero-based, least-squares, straight line method.

[3]Typical.

[4]See PCB Declaration of Conformance PS158 for details.

SUPPLIED ACCESSORIES:

Model 065A06 Seal ring 0.318" OD x 0.250" ID x 0.010" thk 316L SS material (3)

Model 065A19 Spacer set, 0.250" ID (1)

Model PCS-1BD Deadweight and dynamic calibrations to full scale measurement range – two calibration certificates supplied

Entered: ND	Engineer: RPF	Sales: MV	Approved: RPF	Spec Number:
Date: 08/27/2024	Date: 08/27/2024	Date: 08/27/2024	Date: 08/27/2024	61551

Phone: 716-684-0001
 Fax: 716-684-0987
 E-Mail: info@pcb.com

3425 Walden Avenue, Depew, NY 14043



All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.
 ICP® is a registered trademark of PCB Piezotronics, Inc.