

Performance	ENGLISH	SI	
Measurement Range(for ±5V output)	250 psi	1,724 kPa	
Useful Overrange(for ± 10V output)	500 psi	3,448 kPa	[1]
Sensitivity(± 15 %)	20 mV/psi	2.90 mV/kPa	
Maximum Pressure	5,000 psi	34,475 kPa	
Resolution	0.005 psi	0.034 kPa	[2]
Resonant Frequency	≥ 25 kHz	≥ 25 kHz	[3]
Rise Time(Reflected)	≤ 20 μ sec	≤ 20 μ sec	[3]
Low Frequency Response(- 5 %)	0.50 Hz	0.50 Hz	
Non-Linearity	≤ 1.0 % FS	≤ 1.0 % FS	[4]
Environmental			
Acceleration Sensitivity	≤ 0.002 psi/g	≤ 0.0014 kPa/(m/s ²)	
Temperature Range(Operating)	-100 to +250 °F	-73 to +121 °C	[5]
Temperature Coefficient of Sensitivity	≤ 0.03 %/°F	≤ 0.054 %/°C	
Maximum Flash Temperature	10,000 °F	5,538 °C	
Maximum Vibration	2,000 g pk	19,600 m/s ² pk	
Maximum Shock	10,000 g pk	98,070 m/s ² pk	
Electrical			
Output Polarity(Positive Pressure)	Positive	Positive	
Discharge Time Constant(at room temp)	≥ 1.0 sec	≥ 1.0 sec	
Excitation Voltage	20 to 30 VDC	20 to 30 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Impedance	≤ 100 Ohm	≤ 100 Ohm	
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC	
Physical			
Housing Material	17-4 Stainless Steel	17-4 Stainless Steel	
Diaphragm	Invar	Invar	
Sealing	Epoxy	Epoxy	
Electrical Connector	Integral Cable	Integral Cable	
Weight	4.23 oz	120 gm	
Helium Flow Rate(at 1,500 psi)	40 scf/hr	1.13 m ³ /hr	
Cable Length	4 ft	1.2 m	
Water Flow Rate(at 50 psi)	1.2 gal/min	4.5 L/min	

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

[1]For +10 volt output, minimum 24 VDC supply voltage required. Negative 10 volt output may be limited by output bias.

[2]Typical.

[3]With helium flow.

[4]Zero-based, least-squares, straight line method.

[5]Applies to internal amplifier, not to external housing.

[6]See PCB Declaration of Conformance PS023 for details.

SUPPLIED ACCESSORIES:

Model 065A15 Seal, .624" OD x .553" ID x .080", brass (3)

Model 070A08 Cable adaptor (micro 10-32 jack to BNC jack) (1)



Entered: LK	Engineer: NJL	Sales: MV	Approved: RPF	Spec Number:
Date: 12/23/2020	Date: 12/23/2020	Date: 12/23/2020	Date: 12/23/2020	123-1210-80

Phone: 716-684-0001
Fax: 716-684-0987
E-Mail: info@pcb.com

3425 Walden Avenue, Depew, NY 14043

All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.
 ICP[®] is a registered trademark of PCB Piezotronics, Inc.