



Model Number 378C20	ICP MICROPHONE SYSTEM			Revision: F ECN #: 50805										
Performance Nominal Microphone Diameter Frequency Response Characteristic Sensitivity(± 1.5 dB) Sensitivity Frequency Range(± 2 dB) Frequency Range(± 1 dB) Lower Limiting Frequency(- 3 dB) Inherent Noise Dynamic Range(3% Distortion Limit) TEDS Compliant	ENGLISH 1/2" Random Incidence - 26 dB re 1 V/Pa 50 mV/Pa 3.75 to 16,000 Hz 7 to 6,300 Hz 1.0 to 3.0 Hz 16 dB(A) re 20 µPa 137 dB re 20 µPa Yes	SI 1/2" Random Incidence - 26 dB re 1 V/Pa 50 mV/Pa 3.75 to 16,000 Hz 7 to 6,300 Hz 1.0 to 3.0 16 dB(A) re 20 µPa 137 dB re 20 µPa Yes		OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.										
Environmental Temperature Range(Operating) Temperature Coefficient of Sensitivity(+ 14 to +158°F (- 10 to +70°C)) Static Pressure Coefficient Humidity Coefficient of Sensitivity(0 to 100%, non-condensing) Influence of Axial Vibration(0.1g (1 m/s ²))	-40 to +176 °F 0.005 dB/°F - 0.01 dB/kPa ± 0.001 dB/%RH 63 dB re 20 µPa	-40 to +80 °C 0.009 dB/°C - 0.01 dB/kPa ± 0.001 dB/%RH 63 dB re 20 µPa	 [2] [2] [3] [2][1] [2][1] [1] [2]	NOTES: [1]re 250 Hz [2]Typical. [3]TEDS Capable Digital Communication, compliant with IEEE 1451.4 [4]Prepolarized [5]Venting through Preamp. [6]See PCB Declaration of Conformance PS064 for details.										
Electrical Polarization Voltage Excitation Voltage Constant Current Excitation Output Bias Voltage Maximum Output Voltage Output Impedance	0 V 20 to 30 VDC 2 to 20 mA 10 to 14 VDC ± 7 Vpk < 50 Ohm	0 V 20 to 30 VDC 2 to 20 mA 10 to 14 VDC ± 7 Vpk < 50 Ohm	 [4]	SUPPLIED ACCESSORIES: Model ACS-63 Calibration (with TEDS) of Precision Condenser Microphones and Preamplifiers together (mated pair). (1)										
Physical Housing Material Venting Electrical Connector Mounting Thread(Grid) Size (Diameter x Height)(with grid) Size (Diameter x Height)(without grid) Weight	Stainless Alloy Rear BNC Jack 0.5 - 60 UNS 0.52 in x 3.62 in 0.50 in x 3.58 in 1.63 oz	Stainless Alloy Rear BNC Jack 0.5 - 60 UNS 13.2 mm x 91.9 mm 12.7 mm x 90.9 mm 45.8 gm	 [5] [2]	<table border="1"> <tr> <td data-bbox="1129 1271 1287 1317">Entered: LK</td> <td data-bbox="1287 1271 1444 1317">Engineer: MJN</td> <td data-bbox="1444 1271 1602 1317">Sales: MV</td> <td data-bbox="1602 1271 1759 1317">Approved: NJF</td> <td data-bbox="1759 1271 1917 1317">Spec Number:</td> </tr> <tr> <td data-bbox="1129 1317 1287 1360">Date: 06/08/2020</td> <td data-bbox="1287 1317 1444 1360">Date: 06/08/2020</td> <td data-bbox="1444 1317 1602 1360">Date: 06/08/2020</td> <td data-bbox="1602 1317 1759 1360">Date: 06/08/2020</td> <td data-bbox="1759 1317 1917 1360">59949</td> </tr> </table>	Entered: LK	Engineer: MJN	Sales: MV	Approved: NJF	Spec Number:	Date: 06/08/2020	Date: 06/08/2020	Date: 06/08/2020	Date: 06/08/2020	59949
Entered: LK	Engineer: MJN	Sales: MV	Approved: NJF	Spec Number:										
Date: 06/08/2020	Date: 06/08/2020	Date: 06/08/2020	Date: 06/08/2020	59949										
 <p>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice. ICP[®] is a registered trademark of PCB Piezotronics, Inc.</p>				 Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com 3425 Walden Avenue, Depew, NY 14043										