

Model Number

422E20

## IN-LINE CHARGE AMPLIFIER

Revision: C

ECN #: 23737

**Performance**

	ENGLISH	SI	
Sensitivity ( $\pm 5\%$ ) (Charge Conversion)	4 mV/pC	4 mV/pC	
Input Range (Electrical Charge)	$\pm 625$ pC	$\pm 625$ pC	
Ovrrange	$\pm 3$ V	$\pm 3$ V	
Low Frequency Response (-5 %)	1 Hz	1 Hz	
High Frequency Response (2.2 mA)	50 kHz	50 kHz	[3]
High Frequency Response (4 mA)	75 kHz	75 kHz	[3]
High Frequency Response (20 mA)	100 kHz	100 kHz	[3]
Non-Linearity	$\leq 1.0\%$ FS	$\leq 1.0\%$ FS	

**Environmental**

Temperature Range (Operating)	-65 to +250 °F	-54 to +121 °C	
Temperature Response (Sensitivity Deviation)	<1 %	<1 %	
Maximum Shock	1000 g pk	9810 m/s <sup>2</sup> pk	

**Electrical**

Excitation Voltage	18 to 28 VDC	18 to 28 VDC	
Constant Current Excitation	2.2 to 20 mA	2.2 to 20 mA	
Output Voltage (at specified measurement range)	$\pm 2.5$ Vpk	$\pm 2.5$ Vpk	
Output Impedance	<10 ohm	<10 ohm	
Output Bias Voltage	12.75 to 14.25 VDC	12.75 to 14.25 VDC	
Output Polarity	Inverted	Inverted	
Maximum Input Voltage	30 V	30 V	
Broadband Electrical Noise (1 to 10,000 Hz)	15 $\mu$ V	-96 dB	[1]
Spectral Noise (1 Hz)	10 $\mu$ V/ $\sqrt$ Hz	-100 dB	[1]
Spectral Noise (10 Hz)	0.8 $\mu$ V/ $\sqrt$ Hz	-122 dB	[1]
Spectral Noise (100 Hz)	0.2 $\mu$ V/ $\sqrt$ Hz	-134 dB	[1]
Spectral Noise (1 kHz)	0.07 $\mu$ V/ $\sqrt$ Hz	-143 dB	[1]
Spectral Noise (10 kHz)	0.07 $\mu$ V/ $\sqrt$ Hz	-143 dB	[1]
Discharge Time Constant	$\geq 0.5$ sec	$\geq 0.5$ sec	
Resistance (Minimum required at input)	5,000,000 ohm	5,000,000 ohm	[2]
Source Capacitance Loading	0.0005 %/pF	0.0005 %/pF	

**Physical**

Housing Material	Stainless Steel	Stainless Steel	
Sealing	Welded Hermetic	Welded Hermetic	
Electrical Connector (Input)	2-Pin MIL-C-26482	2-Pin MIL-C-26482	
Electrical Connector (Output)	2-Pin MIL-C-5015	2-Pin MIL-C-5015	
Size (Diameter x Length)	0.62 in x 3.62 in	16 mm x 92.0 mm	
Weight	2.46 oz	69.7 gm	



[4]

All specifications are at room temperature unless otherwise specified.  
In the interest of constant product improvement, we reserve the right to change specifications without notice.

ICP® is a registered trademark of PCB Group, Inc.

**OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

T - TEDS Capable of Digital Memory and Communication Compliant with IEEE P1451.4  
Temperature Range (Operating) -40 to +185 °F -40 to +85 °C  
Output Bias Voltage 13.35 to 14.85 VDC 13.35 to 14.85 VDC

**NOTES:**

- [1] Tested using voltage source and input capacitor equal to the feedback capacitor, to simulate a charge output sensor.  
[2] Not to be used with low values of source resistance such as charge mode sensors at elevated temperatures or contaminated sensor cables (preventing low frequency peaking and/or output bias problems).  
[3] Above stated frequency, the amplifier becomes slew rate limited.  
[4] See PCB Declaration of Conformance PS024 for details.

Entered: <i>JR</i>	Engineer: <i>BJ</i>	Sales: <i>MLA</i>	Approved: <i>CP</i>	Spec Number:
Date: <i>3-1-06</i>	Date: <i>3-3-06</i>	Date: <i>3/6/06</i>	Date: <i>3/7/06</i>	12098

 **PCB PIEZOTRONICS™**  
ELECTRONICS DIVISION  
3425 Walden Avenue, Depew, NY 14043

Phone: 716-684-0001  
Fax: 716-684-0987  
E-Mail: [electronics@pcb.com](mailto:electronics@pcb.com)