



INDUSTRIAL CRYOGENICS

INDUSTRIAL CRYOGENICS

Detect Cavitation, Recirculation & Resonance
In Cryogenic Centrifugal & Reciprocating Pumps

The field of cryogenics is typically defined as beginning at temperatures below $-292\text{ }^{\circ}\text{F}$ ($-180\text{ }^{\circ}\text{C}$). There are several common industrial gases (argon, helium, hydrogen, nitrogen and oxygen) and fuels (liquid natural gas and liquid propane gas) whose boiling point is below this temperature mark, thereby classifying them as cryogens.

These gases and fuels are transported and used in a variety of industrial applications as refrigerants in their liquid state, thereby requiring the use of cryogenic centrifugal and reciprocating pumps to effectively transfer them between cryogenic tanks, double-walled containers with a high vacuum between the walls to reduce heat transfer into the liquid. These applications include:

- Liquefied natural gas (LNG) processing
- Industrial gas processing (argon, helium, hydrogen, nitrogen and oxygen)
- Pharmaceutical production (statin drugs, biotech products such as vaccines)
- Frozen food production/storage

Regardless of whether the cryogenic pump is submerged in the liquid or mounted in an exterior suction vessel, these pumps can suffer the same types of faults as their non-cryogenic equivalents, including:

- Acoustical resonances
- Cavitation
- Impeller eccentricity and imbalance
- Impeller/diffuser clearance
- Oil whirl
- Recirculation
- Structural resonances
- Wear ring clearance



TOP-EXIT CRYOGENIC ICP® ACCELEROMETER FOR PREDICTIVE MAINTENANCE

MODEL 637A06

- Sensitivity: 25 mV/g
- Frequency Response: 4-1500 Hz
- Operating Temperature Range: -320 to $+250\text{ }^{\circ}\text{F}$



SIDE-EXIT CRYOGENIC ICP® ACCELEROMETER FOR PREDICTIVE MAINTENANCE

MODEL 638A06

- Sensitivity: 25 mV/g
- Frequency Response: 4-1500 Hz
- Operating Temperature Range: -320 to $+250\text{ }^{\circ}\text{F}$



CABLES/CONNECTORS FOR CRYOGENIC APPLICATIONS

MODELS 048/053 AE/AP/BP/BQ/BR

- All tested to $-300\text{ }^{\circ}\text{F}$ ($-184\text{ }^{\circ}\text{C}$)

4-20 mA TRANSMITTERS FOR PROCESS MONITORING AND PROTECTION

IMI® 4-20mA vibration transmitters are particularly well-suited for 24/7 vibration monitoring of critical rotating equipment. Simply install the transmitter in conjunction with a cryogenic ICP® accelerometer and run the 4-20 mA output to the nearest PLC, DCS, SCADA, or any plant information system. That is all it takes to begin continuous vibration monitoring and avoid costly unexpected down time. Using the reliable 4-20mA trending signal enables the user to schedule diagnostic testing based on real data rather than using time scheduled route based testing. This practice saves time and reduces overall costs of predictive maintenance. Optional hazardous area approved models also available.



VIBRATION TRANSMITTER

MODEL 682C03

- ICP® accelerometer input
- Outputs 4-20 mA signal proportional to acceleration, velocity, or displacement
- Analog vibration output via front BNC



UNIVERSAL TRANSMITTER

MODEL 682A06 (WITH MODEL 070A80 FRONT PANEL)

- Input 4-20 mA signal from Model 682C03
- Outputs include current re-transmit and two Form A relays
- Fully field-programmable with use of detachable display (Model 070A80)

PORTABLE VIBRATION CALIBRATORS FOR ON-SITE SENSOR VALIDATIONS

If a measurement is taken only to find out later that the sensor was bad, the cost of invalidating the data or re-taking it (if even possible) can range from nothing to immense. Routine calibration of sensors can eliminate this concern by periodically measuring the sensitivity and output of a sensor. Small and completely self-contained, portable vibration calibrators are ideal for field check of accelerometers, velocity transducers and proximity probes.



PORTABLE VIBRATION CALIBRATOR

MODELS 699A06 & 699A07

- Ruggedized, weatherproof enclosure dramatically improves durability and portability
- Precision quartz reference accelerometer and conditioning electronics for superior control and stability
- Provides NIST traceable transducer verification across a wide frequency and amplitude range



HANDHELD SHAKER

MODEL 699B02

- Fixed frequency of 159.2 Hz
- Field-adjustable measurement range in acceleration, velocity, or displacement



3425 Walden Avenue, Depew, NY 14043-2495 USA

Toll-Free in the USA: 800 959 4464

Phone: 1 716 684 0001 | Email: info@pcb.com

IMI Sensors, a division of PCB Piezotronics, Inc. manufactures industrial vibration monitoring instrumentation, such as accelerometers, vibration transmitters and switches that feature rugged stainless steel housings and survive in harsh environments like paper and steel mills, mines, gas turbines, water treatment facilities and power plants. Integrating with portable analyzers and PLC's, IMI instrumentation helps maintenance departments reduce downtime and protect critical machinery. Visit IMI Sensors at www.pcb.com. PCB Piezotronics, Inc. is a wholly owned subsidiary of MTS Systems Corporation. Additional information on MTS can be found at www.mts.com.

© 2019 PCB Piezotronics, Inc. In the interest of constant product improvement, specifications are subject to change without notice. PCB®, ICP®, Swiveler®, Modally Tuned®, and IMI® with associated logo are registered trademarks of PCB Piezotronics, Inc. in the United States. ICP® is a registered trademark of PCB Piezotronics Europe GmbH in Germany and other countries. UHT-12™ is a trademark of PCB Piezotronics, Inc. SensorLine™ is a service mark of PCB Piezotronics, Inc. SWIFT® is a registered trademark of MTS Systems Corporation in the United States.

IMI-App-Cryogenics-0819



MTS Sensors, a division of MTS Systems Corporation (NASDAQ: MTSC), vastly expanded its range of products and solutions after MTS acquired PCB Piezotronics, Inc. in July, 2016. PCB Piezotronics, Inc. is a wholly owned subsidiary of MTS Systems Corp.; IMI Sensors and Larson Davis are divisions of PCB Piezotronics, Inc.; Accumetrics, Inc. and The Modal Shop, Inc. are subsidiaries of PCB Piezotronics, Inc.