



# CRYOGENIC ACCELEROMETERS & PRESSURE SENSORS

---

## CRYOGENIC ICP® ACCELEROMETERS

Cryogenic ICP® accelerometers are specifically designed to operate at temperatures below the typical -65 °F (-54 °C) temperature limit of most voltage mode sensors. The use of specialized, built-in, cryogenic ICP® circuitry and quartz shear sensing technology provides survivability in demanding environments such as liquid nitrogen. Each sensor is hermetically sealed and individually tested to determine the thermal coefficient of sensitivity at -320 °F (-196 °C) ensuring reliable operation and accurate measurements. Choose from a variety of accelerometers ranging from lightweight units for minimizing mass loading effects to high sensitivity versions for sensing low-level vibrations.



CRYOGENIC ICP® ACCELEROMETERS					
Model Number	PCB 351B03	PCB 351B04	PCB 351B31	PCB 351B41	PCB 351B42
Performance					
Sensitivity	10 mV/g (1.02 mV/(m/s²))		50 mV/g (5.10 mV/(m/s²))	100 mV/g (10.2 mV/(m/s²))	
Measurement Range	±150 g pk (±1472 m/s² pk)		±30 g pk (±294 m/s² pk)	±15 g pk (±147 m/s² pk)	
Frequency Range (±5%)	1 - 6000 Hz		1 - 4000 Hz	1 - 2000 Hz	
Options: Available with ground isolation	J351B03	J351B04	J351B31	J351B41	J351B42



CRYOGENIC MINIATURE ICP® ACCELEROMETERS			
Model Number	PCB 351B11	PCB 351B14	PCB 351A15
Performance			
Sensitivity	5 mV/g (0.51 mV/(m/s²))		5.5 mV/g (0.56 mV/(m/s²))
Measurement Range	±300 g pk (±2943 m/s² pk)		±1000 g pk (±9810 m/s² pk)
Frequency Range	1 - 10000 Hz	1 - 8000 Hz	1.25 to 6500 Hz
Options: Available with ground isolation	J351B11	J351B14	-
Options: Available in Metric	M351B11	M351B14	-

CRYOGENIC TRIAXIAL ICP® ACCELEROMETER	
Model Number	PCB 354A14
Performance	
Sensitivity	10 mV/g (1.02 mV/(m/s²))
Measurement Range	±500 g pk (±4905 m/s² pk)
Frequency Range	5000 - 10000 Hz

## CRYOGENIC CHARGE OUTPUT PIEZOELECTRIC ACCELEROMETERS

Endevco® cryogenic piezoelectric accelerometers are built specifically for measuring vibration under cryogenic conditions down to -452 °F (-269 °C). Signal outputs of these units are very stable even at extremely low temperatures. Their rugged internal construction is designed to withstand multiple cycles of thermal shock with steep temperature gradient. The accelerometers are self-generating devices that require no external power source for operation and contain no electronics. This allows them to operate below the -320 °F (-196 °C) limit of ICP accelerometers, down to -452 °F (-269 °C).



CRYOGENIC CHARGE OUTPUT PIEZOELECTRIC ACCELEROMETERS			
Model Number	Endevco 7722	Endevco 7724	Endevco 2271A / 2271AM20
Performance			
Description	Immune to thermal transients, grounded design	Immune to thermal transients, isolated design	High sensitivity, side (2271A) or top exit (2271AM20) connector
Sensitivity (pC/g typical)	3.7	3.7	11.5
Sinusoidal Limit (g)	500	500	1000
Shock Limit (g)	2500	2500	10000
Frequency Response (±1 dB Hz)	1 - 6000	1 - 6000	1 - 8000



REMOTE CHARGER CONVERTERS WITH TEDS			
Model Number	Endevco 2771C-01	Endevco 2771C-1	Endevco 2771C-5
Performance			
Gain	.1 mV/pC	1 mV/pC	5 mV/pC
Input Type	Single-ended piezoelectric	Single-ended piezoelectric	Single-ended piezoelectric
Number of channels	1	1	1
Configuration	In-line	In-line	In-line

# CRYOGENIC DYNAMIC PRESSURE SENSORS

The 102B1x Series ICP® pressure sensors feature ground isolation and low operating temperature capability ideal for measuring cryogenic pumps, cryogenic fuel systems, and rocket motor combustion instability. Each sensor is hermetically sealed and individually tested to determine the thermal coefficient of sensitivity at -320 °F (-196 °C) ensuring reliable operation and accurate measurements. PCB Models 112B05 & 112A06 are unique in their ability to withstand both extreme cold and extreme heat.



CRYOGENIC ICP® PRESSURE SENSORS				
Model Number	PCB 102B13	PCB 102B14	PCB 102B11	PCB 102B10
Performance				
Sensitivity	0.5 mV/psi (0.073 mV/kPa)	1 mV/psi (0.145 mV/kPa)	5.0 mV/psi (0.725 mV/kPa)	50 mV/psi (7.25 mV/kPa)
Measurement Range	10 kpsi (68950 kPa)	5 kpsi (34475 kPa)	1 kpsi (6895 kPa)	100 psi (690 kPa)
Resonant Frequency	≥250 kHz	≥250 kHz	≥250 kHz	≥250 kHz
Mounting Thread	3/8-24	3/8-24	3/8-24	3/8-24



CRYOGENIC ICP® PRESSURE SENSORS			
Model Number	PCB 102M81A	PCB 102M80A	PCB 102M295 (Ground Isolated)
Performance			
Sensitivity	10 mV/psi (1.45 mV/kPa)	50 mV/psi (7.25 mV/kPa)	1.5 mV/psi (0.218 mV/kPa)
Measurement Range	500 psi (3447 kPa)	100 psi (690 kPa)	3500 psi (24132 kPa)
Resonant Frequency	≥250 kHz	≥250 kHz	≥250 kHz
Mounting Thread	7/16-20 UNF - 2A	7/16-20 UNF - 2A	7/16-20 UNF



CRYOGENIC CHARGE OUTPUT PRESSURE SENSOR		
Model Number	PCB 112B05	PCB 112A06
Performance		
Sensitivity	1.1 pC/psi (.16 pC/kPa)	2.6 pC/psi (0.44 pC/kPa)
Measurement Range	5000 psi (34475 kPa)	5000 psi (34475 kPa)
Resonant Frequency	≥200 kHz	≥200 kHz
Mounting Thread	5/16-24	5/16-24
Temperature Range	-400 to 500°F (-240 to 260°C)	-400 to 662°F (-240 to 350°C)



## LOW NOISE COAXIAL CABLE

PCB MODEL 003A

- Blue TFE jacket
- 10-32 plug to 10-32 plug
- Temperature range: -320 to +500°F (-196 to +260 °C)
- 1 - 100 ft. options available



## LOW NOISE COAXIAL CABLE

PCB MODEL 003G

- Blue TFE jacket
- 5-44 plug to 10-32 plug
- Temperature range: -320 to +500°F (-196 to +260 °C)
- 3 - 30 ft. options available



## LOW NOISE COAXIAL CABLE

ENDEVCO MODEL 3090C

- Red PTFE jacket
- 10-32 plug to 10-32 plug
- Temperature range: -452 to +500°F (-269 to +260 °C)
- 1 - 50 ft. options available





**3425 Walden Avenue, Depew, NY 14043 USA**

pcb.com | info@pcb.com | 800 828 8840 | +1 716 684 0001



**10869 NC Highway 903, Halifax, NC 27839 USA**

endevco.com | sales@endevco.com | 866 363 3826

© 2025 PCB Piezotronics - all rights reserved. PCB Piezotronics, Inc. is a wholly-owned subsidiary of Amphenol Corporation. Endevco is an assumed name of PCB Piezotronics of North Carolina, Inc., which is a wholly-owned subsidiary of PCB Piezotronics, Inc. Accumetrics, Inc. and The Modal Shop, Inc. are wholly-owned subsidiaries of PCB Piezotronics, Inc. IMI Sensors and Larson Davis are Divisions of PCB Piezotronics, Inc. Except for any third party marks for which attribution is provided herein, the company names and product names used in this document may be the registered trademarks or unregistered trademarks of PCB Piezotronics, Inc., PCB Piezotronics of North Carolina, Inc. (d/b/a Endevco), The Modal Shop, Inc. or Accumetrics, Inc. Detailed trademark ownership information is available at [www.pcb.com/trademarkownership](http://www.pcb.com/trademarkownership).

AD-Cryogenic-0125